



Main

Accessory / separate part category	Communication accessory
Accessory / separate part type	Wireless access point
Accessory / separate part destination	Smart phone
Operating Distance	10 m

Complementary

Range Compatibility	Easergy
Kit composition	Battery
Function Available	Configure over bluetooth Automatic/OFF Optional communication kit for remote monitoring Serial link kit Standalone operation with power supply unit possible
Connector type	Male SUB-D 9 Mini DIN USB device port Mini-B USB type B SUB-D 9, mini-DIN and USB
Communication port protocol	NFC Bluetooth 4.2 (BLE)
Operating System	Android Mac iOS
System Requirements	Google Chrome Firefox
Supply	Li battery USB interface of the PC
Local signalling	For power ON 1 LED (green) For battery status 1 LED (green/red) For activity detected 1 LED (white)
Net Weight	0.30 lb(US) (0.134 kg)

Environment

IP Degree of Protection	IP20
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Relative humidity	10...90 % operation, without condensation IEC 60068-2-3
Product Certifications	FCC CE

Ordering and shipping details

Category	22159-ATV212 OPTIONS
Discount Schedule	CP4D
GTIN	3606489817053
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------