



- NOTES:
1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. RATING: 50mA, 12VDC
4. TRAVEL: 0.2 ± 0.1
5. OPERATING FORCE: 160 ± 50 gf
6. CONTACT RESISTANCE: 100m-Ohms MAX
7. CONTACT MATERIAL: SILVER
8. OPERATING LIFE: 500,000 CYCLES
9. INSULATION RESISTANCE: 100M-Ohms MIN
10. DIELECTRIC STRENGTH: 500VDC FOR 1 MINUTE
▲ 11. LED COLOR: BLUE
12. OPERATING TEMPERATURE: -40° C to 85° C
13. 2011/65/EU (ROHS) COMPLIANT
14. ▲ DENOTES CRITICAL PARAMETER

▲ LED SPECS	UNITS	BLUE LED
FORWARD CURRENT	mA	20
FORWARD VOLTAGE	V	3.1 TYP. - 3.8 MAX
LUMINOUS INTENSITY	mcd	1300 TYP.

D	23698	update, Dim. 12.00 to 11.90, 4.50 to 4.40	12/10/18	MW
C	19925	REVISED AND REDRAWN	05/09/11	BMA
B	19526	ADD DIMS	12/14/10	BMA
REV	PCR NO	DESCRIPTION	DATE	BY



TITLE TL1265BQSCLR				
SCALE 3:1	DATE 12/8/2010	DR BA	DWG B200018	REV D