



SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item ㉑ Terminal(housing) : PA66 (UL94V-0)
- Item ㉒ Terminal(cover) : PA66 (UL94V-0) (ET 7.62)
- Item ㉓ Terminal screw : Steel Zinc plating " - " slot type (ET 7.62)
- Item ㉔ Clamp : Brass, Ni plated (ET 7.62)
- Item ㉕ Female contact : Copper, Tin plated
- Item ㉖ With flange Nut : Steel Zinc plating M3 (VC 7.62)

Electrical

- Voltage rating: 600VAC
- Current rating: 41A
- Solid wire (AWG): 8-24
- Stranded wire(AWG): 8-24
- Torque: 9.0 Lb-In
- Screw: M3.5
- Wire strip length: 10-11mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: 
- Critical dimension: 

KT xx 0 1 x 2 xxxx G

No. OF POLES
02: 2 POLES
:
16: 16 POLES

G: Pb=40000ppm
0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request.
please contact sales department.

COLOR
0 Black (RAL9005)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
C Green(RAL6018/U)

N = Number of poles

Dimension

Dim.A	N × 7.62
Dim.B	(N-1) × 7.62
Dim.C	(N+1) × 7.62
Dim.D	(N + 2) × 7.62

Poles	Tolerance
2P-5P	±0.20
6P-10P	±0.30
11P-16P	±0.40

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		KT 7.62 Series 2P-16P " - " Screw (Flange With Nut)					
PART NO.		KTxx01x2xxxxG		DWG NO.		8KT0014	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Aaron 2011.10.18	Aaron 2011.10.18			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
				SHEET: 01/01		UNIT: mm SCALE: NONE REV.: B	