

Product data sheet

Characteristics

NSYVEA9

Water drain plug, for drainage of condensation water. Drilling diam: 8.5 mm.IP53



Main

Range	Thalassa
Range compatibility	Thalassa PLM
Product or Component Type	Plug
Accessory / separate part category	Thermal management accessory
Environmental characteristic	Water resistant
Mounting Location	Bottom of enclosure
Fixing Mode	Clipped
Device composition	1 plug
Quantity per Set	Set of 10

Complementary

Diameter	0.32 in (8.2 mm) PLM 0.33 in (8.5 mm)
IP degree of protection	IP53category 2)

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480192975
Nbr. of units in pkg.	10
Package weight(Lbs)	0.02 lb(US) (0.01 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.35 in (0.9 cm)
Package 1 width	0.71 in (1.8 cm)
Package 1 Length	0.71 in (1.8 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	0.39 oz (11 g)
Package 2 Height	0.79 in (2 cm)
Package 2 width	1.18 in (3 cm)
Package 2 Length	3.15 in (8 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------