

Eaton Internal Replacement Battery Cartridge (RBC) for Select 1500VA 9PX UPS Systems and EBMs

MODEL NUMBER: 744-A3297



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton 9PX UPS system or EBM.

Features

UPS Replacement Battery Cartridge for Select Eaton 9PX UPS Systems

This UPS backup battery replacement is compatible with Eaton's 9PX1500RT, 9PX1500RTN and 9PX1500GRT UPS systems and 9PXEBM48RT extended battery module (EBM). Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A3297 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A3297 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your 9PX UPS system.

Specifications

| OVERVIEW | |
|--------------|----------------------------------|
| UPC Code | 743172089762 |
| INPUT | |
| Input Phase | Single-Phase |
| BATTERY | |
| Battery Type | Valve Regulated Lead Acid (VRLA) |

Highlights

- Replacement battery backup for select Eaton 1.5kVA 9PX UPS and EBMs
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships ready for immediate UPS installation to prevent downtime

System Requirements

Compatible only with Eaton's 9PX1500RT, 9PX1500RTN and 9PX1500GRT UPS systems and 9PXEBM48RT EBM

Package Includes

744-A3297 Internal Replacement Battery Cartridge



Powering Business Worldwide

1000 Eaton Boulevard
Cleveland, OH 44122
United States

| | |
|-----------------------------------|---|
| Battery Replacement Description | Re-use existing wiring harness |
| Hot Swap Battery | Yes |
| PHYSICAL | |
| Unit Dimensions (hwd / in.) | 4.000 x 14.000 x 10.000 |
| Unit Weight (lbs.) | 23.1 |
| Unit Weight (kg) | 10.48 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| APPLICATIONS | |
| Used With | 9PX1500RT, 9PXEBM48RT, 9PX1500GRT, 9PX1500RTN |
| STANDARDS & COMPLIANCE | |
| Product Certifications | UL Listed; cUL Listed |
| Product Compliance | FCC (USA); CE (Europe) |



Powering Business Worldwide

© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.