



Pantone 577C (green)
Colored Barrel Cover
(See PC99 Spec. For
Color Details)



Recommended PCB Layout
(Bottom View)

Materials and Finish

Housing & Barrel Cover:
PBT Thermoplastic, 15% Glass Filled,
UL 94V-0 Rated, Black Housing,
Pantone 577C Color Barrel Cover,
(See PC99 Spec. for Details)

Terminals:
Pin #1 : Brass, Nickel Plated
Pin #5 & Pin #2 :
Phosphor Bronze, Matte Tin Plated

Bushing: Brass, Nickel Plated

Electrical Characteristics

Rated Voltage: DC 24 V
Rated Current: 3.0 A
Contact Resistance:
Before Test: 50mohms Max.
After Durability Test: 100 mohms Max.

Insulation Resistance:
More Than 100 Megohms
At 500V DC

Dielectric Strength:
500V AC RMS for 1 Minute

Operating Temp: -25°C to +85°C

Mechanical Characteristics

Insertion Force: 0.3kg - 3.0kg

Extraction Force: 0.3kg - 3.0kg

Durability: 5000 Mating Cycles Min.

Tolerances

X.X ± 0.3
X.XX ± 0.15
Unless Stated
Otherwise



REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	9/6/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	07/11/05
A2	11/30/06	ECO 06-046	R. Aguirre	H. MA		
A3	07/14/11	ECO #11-033	S. Vien	P. DalCanto		
A4	08/14/18	Update Address	D. Shehan	N/A		
A5	04/22/19	ECO #19-035	C. Kelleher	D. Shehan		

STX-3100-3N-577C

Ø3.5mm Stereo Jack, Right Angle, Thru-Hole, RoHS Compliant

3 Position, w/ PC99 Color (Green) Barrel Cover

