



- SPECIFICATIONS:**
- MATERIAL:
    - (A) BODY: PA66 (UL 94V-0)
    - (B) COVER: PBT (UL 94V-0)
    - (C) LONG TERMINAL: BRASS
    - (D) SHORT TERMINAL: BRASS
  - ELECTRICAL RATING: 300V, 15A
  - DIELECTRIC WITHSTAND: AC 2500V FOR 1 MINUTE
  - BREAKDOWN VOLTAGE: 4000V
  - INSULATION RESISTANCE: DC 1000V, 1000 MEGOHMS.
  - OPERATING TEMPERATURE: -40°C TO +105°C.
  - NUMBER OF CIRCUIT POSITIONS AVAILABLE= 4 THROUGH 48, EVEN NUMBERED CIRCUIT SIZES ONLY.
  - ALL COMPONENTS ARE ROHS COMPLIANT.
  - DIMS SHOWN ARE FOR REFERENCE ONLY.

TOLERANCES			
MM	TOL	INCH	TOL
0-6	±0.25	0-.24	±.010
>6-30	±0.40	.24-1.18	±.016
>30-120	±0.50	1.18-4.76	±.020
>120	±0.80	>4.76	±.031

SYMBOLS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
▽ = 0	MM/INCH	SCALE	3:1
▽ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		
▽ = 0	4 PLACES ±	MM	INCH
▽ = 0	3 PLACES ±	SEE CHART	SEE CHART
▽ = 0	2 PLACES ±	SEE CHART	SEE CHART
▽ = 0	1 PLACE ±	SEE CHART	SEE CHART
▽ = 0	0 PLACES ±	SEE CHART	SEE CHART
⊠ = 0	ANGULAR TOL		±
■ = 0	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		
▽ = 0	THIRD ANGLE PROJECTION	DRAWING	SERIES
	⊕	B-SIZE	39528
CURRENT REV DESC: MIGRATION TO ECTR/NX		EC NO: 620717	
		DRWN: ABENJAMINLW	2019/07/12
		CHK'D: DACHAMMER	2019/07/16
		APPR: JFMURPHY	2019/08/02
		INITIAL REVISION:	
		DRWN: CYORK	2006/07/25
		APPR: JPAWLICK	2006/07/26
DOCUMENT NUMBER		DOC TYPE	DOC PART
SD-39528-002		PSD	001
REVISION		A2	
MATERIAL NUMBER		CUSTOMER	SHEET NUMBER
SEE SHEET-2		GENERAL MARKET	1 OF 2

