



Ethernet Switch

Ha-VIS mCon 7100-AAV

10-port Ethernet Switch for use in harsh industrial environments, with 2 Gigabit ports

Managed	IP65 / IP67	PROFINET compatible <input checked="" type="checkbox"/>	EtherNet/IP compatible <input checked="" type="checkbox"/>
Number of ports, Copper / Termination	8x 10/100Base-T(X) / Han® 3 A RJ45 (female) 2x 10/100/1000-Base-T(X) / Han® 3 A RJ45 (female)		
Input voltage / Termination	24 / 48 V DC / Han® 4 A, male, for redundant power supply		
Permissible range (min./max.)	12 V ... 60 V DC		
Input current	approx. 260 mA (at 24 V DC)		
Alarm signalling contact	Change-over contact, potential-free, 24 V DC / 0.5 A Han® 3 A, male		
Housing material	zinc die-cast		
Dimensions (W x H x D)	90 x 120 x 87 mm		
Weight	approx. 1.4 kg		
Working temperature	-40 °C ... +70 °C		
Management	fully managed via Web interface and SNMP Functions see pages 01.141 and 01.142		

Identification	Part number	Drawing	Dimensions in mm
Ha-VIS mCon 7100-AAV Ethernet Switch with 10 RJ45 ports	20 70 310 4924		