

# IIoT Product End-of-Life Notice

## End of Life, Last Time Buy and Replacement Announcement

Dear Valued Customers:

For immediately release, Advantech is announcing the End of Life (EOL) of **WOP-3070T-C4BE series** and related T-P/N and CTOS P/N. The relative replacing models are as below list. Customers who had purchased this Part Number either to purchase any additional rules or migrate to the new replacement models if possible before the EOL's shipment date.

### Product Part Numbers Affected by This Announcement

| End of Life Product | Suggest Replacement Product |
|---------------------|-----------------------------|
| WOP-3070T-C4BE      | TPC-71W-N21PA               |
| WA-HT3070T-R15H0AE  | -                           |

### Reason for the Change

- Product Enhancement

### Key Milestones / Schedule Dates



| Important Date | Description   | Date      |
|----------------|---|-----------|
| Phase-out      | The product is officially phased out.   | 2021/9/30 |
| LTB            | Last time buy for customer order. After this date, no more order will be accepted.                      | 2022/3/31 |
| Last Shipment  | Acceptable shipment date before LTB. The order with requesting DD after this date will not be accepted. | 2022/6/30 |

## Key Specification Comparison

|                | TPC-71W-N21PA                                       | WOP-3070T-C4BE  |
|----------------|---|---|
| CPU            | Cortex-A9 1GHz Dual/Quad Core 32-bit                | Cortex-A8 600MHz 32-bit   |
| Storage & RAM  | 8G eMMC & 2G DDR3                                   | 512MB Micro-SD card & 256MB DDR2  |
| OS Support     | Linux Ubuntu 16.04/ Android 6/ WEC7                 | Win CE 6  |
| SD card        | 1 x Micro-SD Slot                                   | 1 x Micro-SD Slot   |
| USB            | 1 x USB 2.0 Type-B Client & 2 x USB 2.0 Type-A Host | 1 x USB 2.0 Type-B Client & 1 x USB 2.0 Type-A Host   |
| LAN            | 1 x RJ45 with 10/100/1000 Mbps LAN                  | 1 x RJ45 with 10/100 Mbps LAN   |
| COM            | COM1:RS232/485/CAN                                  | COM1: RS-232/422/485 (DB9 Male)<br>COM2: RS-422/485 (Terminal Plug 4-Pin)<br>COM3: RS-485 (Terminal Plug 2-Pin) |
| WiFi&BT        | 1 x mPCIe slot                                      | NA  |
| NFC            | 1 x internal USB port                               | NA  |
| POE Module     | IEEE 802.3af PoE /802.3at PoE+ PD standard          | NA  |
| Panel          | 7" WSVGA  | 7" WVGA   |
| Resolution     | 1024 x 600  | 800 x 480   |
| Backlight Life | 50,000 hrs  | 50,000 hrs  |
| Operating Temp | -20 ~ 60 °C   | -20 ~ 60 °C   |
| IP Rating      | IP66  | IP66  |
| Mounting       | Panel / VESA  | Panel   |

## Contact Windows

|     |   |
|-----|---|
| PM  | Chia.Tu #511-7108, <a href="mailto:chia.tu@advantech.com.tw">chia.tu@advantech.com.tw</a> |
| SAE | ASG.ACL.PAE <a href="mailto:ASG.ACL.PAE@advantech.com">ASG.ACL.PAE@advantech.com</a>      |