


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 28.5              |
| B   | 23                |
| C   | 3.2               |
| D1  | 22.23             |
| D2  | 20.5              |
| E   | 0.46              |
| K   | 3.89              |
| L1  | 34                |
| L2  | 11.6              |
| L3  | 1.9               |
| L4  | 21.1              |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 1   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 2   | ISOLIERKÖRPER MITTE / WAVER             |
| 3   | DICHTRING / GASKET                      |
| 4   | DICHTKÖRPER / GROMMET                   |
| 7   | KONTAKT BUCHSE / CONTACT SOCKET         |
| 8   | GEHÄUSE / RECEPTACLE                    |
| 19  | BAYONETTSTIFT / BAYONET PIN             |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

| Material Specification: |  |
|-------------------------|--|
| Shell Material:         | Aluminium alloy                                  |
| Shell Plating:          | Olive drab chromate over cadmium plating         |
| Insulator Material:     | Polychloroprene                                  |
| Contact Material:       | Copper alloy                                     |
| Contact Plating:        | #12/16:gold plated, #20:contact area gold plated |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER

**ITT**  
*Engineered for life*  
 ITT CANNON GmbH  
 D - 71384 Weinstadt/Germany

description **MS3122E14-19S**  
 Box mounting receptacle  
 Crimp Contacts / Socket / Layout: 14-19