



- 1 PLUG ACCEPTS SIZE 20 PIN CONTACTS (CONTACTS MUST BE ORDERED SEPARATELY).
- 2. ALL PARTS SHIPPED UNASSEMBLED, EACH PART INDIVIDUALLY BULK PACKED.
- 3 SHIELDS: MATERIAL—.020 THICK STEEL, PER ASTM A109, PLATED .000200 MIN TIN OVER .000100 MIN COPPER UNDERPLATE.
- 4 RAISED CAVITY IDENTIFICATION AND AMP TRADEMARK.

1658652-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN J. REITZEL 31JUL03	STE TE Connectivity	
DIMENSIONS: INCHES		CHK S. BOLASH 31JUL03	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APP'D M. WALMSLEY 31JUL03	KIT, PLUG, SHIELDING HARDWARE, SIZE 5, 50 POSN, AMPLIMITE HDP-20	
0. PLC ± -	1. PLC ± -	PRODUCT SPEC	108-40030	
2. PLC ± -	3. PLC ± .005	APPLICATION SPEC	114-40030	
4. PLC ANGLES ± -	± 0° 30'	SIZE	CAGE CODE	DRAWING NO
MATERIAL SEE CALL OUT	FINISH SEE CALL OUT	WEIGHT	A1	00779
CUSTOMER DRAWING		SCALE	2:1	SHEET 1 OF 1