

APPLICATOR PARTS LIST

TYPE RING
LENGTHWISE - (5 Ton Benchmaster)

AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER	1	453929-1	42			
2	INS. CRIMPER			43			
3	ANVIL	1	371678-2	44			
4	ANVIL SPACER			45			
5	SHEAR BLADE	1	372733	46			
6	REAR SHEAR PLATE	1	370484-1	47			
7	SHEAR BLADE SPACER	2	370748	48			
8	FRONT SHEAR PLATE			49			
9	REAR ANVIL SPACER PLT.	1	385528	50			
10	FRONT ANVIL SPACER PLT.			51			
11	TOOL SPACER	1	374758	52			
12	CRIMP SPACER			53			
13	FRONT STRIP GUIDE	1	371584	54			
14	REAR STRIP GUIDE	1	371584	55			
15	RAM			56			
16	TOOL HOLDER	1	465308-1	57	Mount-Operating Bracket	1	811353-1
17	ADJ. CRIMP MOUNT			58	Bracket-Operating	1	811354-1
18	ADJ. BLOCK			59	PLATE, WASHER	2	694783-1
19	APPLICATOR MOUNT ASSY.	1	570703-1	60			
20	BASE PLATE			61			
21	BASE BLOCK			62			
22	STRIP GUIDE PLATE			63			
23	ANVIL HOLDER	1	372584	64	AIR FEED ASSY	1	690021-3
24	AUX. ANVIL HOLDER	1	377515	65	TENSION ADJ. PLATE	1	374999
25	STRIPPER	1	376987		MISCELLANEOUS		
26	STRIPPER MOUNT	1	370660	66	LUBRICATOR ASSY.	1	464519-2
27	RETAINER PLATE	1	372251	67	SYNTHETIC OIL	1	22014-1
28	STRIPPER MOUNT BRACKET			68	SPACER LUBRICATOR	1	454400-1
29	STRIPPER BUSHING			69	SPACER	2	21800-2
30	STOCK DRAG	1	376666	70			
31	STOCK DRAG HANDLE			71			
32	STOCK DRAG STUD	2	354045-1	72			
33	STOCK DRAG SPRING	2	1-23847-0		REV. REVISION RECORD	DATE	BY ECN
34	STOCK DRAG ADJ. SCREW	2	372997	B	ITEM 3 WAS -1	12/26	DP L-4140
35	FEED FINGER HOLDER			C	ITEM 6 WAS 370484	7/2/66	DP M L-4215
36	FEED FINGER	1	375093	D	PARTS LIST 5TON WAS 565433-2	3-12-70	DP L-7422
37	FEED FINGER TIP			D	ADD 65, FEED 690021-3, 33		
38	FEED FINGER SPACER			E	ITEM 36 WAS 210593-1	2-28-71	IM L-8307
39	BASE CASTING	1	565154-3	F	REV ITEM (1)	5-24-71	IM L-8312
40	GUARD	1	460677-1	G	DELETE ITEM 31 370951	12-5-72	RE M L-9321
41				H	ADD 66 & 67	4-23-73	RE M L-9680
				J	REV. PER ECN	9-7-73	JW R22
				K	REV ITEM #40	10/14/75	LE R1339
				L	ECN A-395872	9-92	MO TB

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. NO CHANGE OR SUBJECT TO CHANGE PERMITTED WITHOUT THE WRITTEN AUTHORIZATION OF THE COMPANY. THIS DRAWING SHOULD BE CONTACTED FOR THE LATEST REV. 5/10/01

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL			L0797- L0974-
WIRE SIZE	CRIMP HEIGHT		
#8	.151		
#10	.132		
CRIMP WIRE	SIZE	TYPE	FEED
	.280	"R"	1.009
INSUL.			
SLEEVED	OVER .275	ANVIL	
INSULATION RANGE	WIRE RANGE #8 - #10		
EXPLODED VIEW	A-6000, -1 A-6034-2		
REMARKS:	<p>■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT</p> <p>THIS APPLICATOR IS TO BE USED ON 5 TON BENCHMASTER 565433-4</p> <p>AIR FEED 690021-3</p> <p>Alignment G: 679597-1</p> <p>CUSTOMER NAME AND ADDRESS: Antinacher</p> <p>APPLICATOR NUMBER: N REV. 671877-4</p>		
SERIAL NO.	DATE SHIPPED	DESIGNED	DIST. 4
		11-21-64	
CUSTOMER NAME AND ADDRESS			CHK'D. 11-24-64
			APP'D. 11-24-64
APPLICATOR NUMBER	REV.	SHEET	1 OF 4