

R73RW3560SE00K

Aliases (73RW3560SE00K)

R73, Film, Film/Foil Polypropylene, General Purpose, 0.56 uF, 10%, 1250 VDC, 85°C, Lead Spacing = 37.5mm



Click here for the 3D model.

Dimensions	
L	41.5mm +0.3/-0.7mm
Н	40mm +0.1/-0.7mm
т	20mm +0.3/-0.7mm
S	37.5mm +/-0.4mm
LL	4mm +2mm
F	1mm +/-0.05mm

Packaging Specifications		
Packaging	Tray	
Packaging Quantity	126	

General Information		
Series	R73	
Dielectric	Film/Foil Polypropylene	
Style	Radial	
Features	Pulse	
RoHS	Yes	
Lead	Cut	
AEC-Q200	No	
Component Weight	39.84 g	
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C.	

Specifications			
Capacitance	0.56 uF		
Capacitance Tolerance	10%		
Voltage AC	450 VAC		
Voltage DC	1250 VDC		
Temperature Range	-55/+105°C		
Rated Temperature	85°C		
Dissipation Factor	0.03% 1kHz, 0.06% 10kHz		
Insulation Resistance	53.5714 GOhms		
Max dV/dt	5500 V/us		
Inductance	20 nH		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.