



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-----------------|
| L | 10.6mm +/-0.3mm |
| W | 5.7mm +/-0.3mm |
| H | 8.8mm MAX |
| LL | 3.4mm NOM |
| S | 3.2mm +/-0.15mm |
| S1 | 2.2mm +/-0.15mm |
| F | 0.8mm +/-0.1mm |
| F1 | 3.1mm +/-0.1mm |

Packaging Specifications

| | |
|-----------|------|
| Packaging | Tube |
|-----------|------|

General Information

| | |
|-------------|---|
| Series | UB2 |
| Style | SMD |
| Description | Miniature Signal Relay, Non-latch Low Power Consumption |
| Features | Super-Compact Size, Flat-Package |
| RoHS | Yes |
| Coil Type | Single Coil (Non-Latching) |

Specifications

| | |
|-------------------------|--------------------------------------|
| Temperature Range | -40/+85°C |
| Coil Voltage | 3 V |
| Coil Resistance | 90 Ohms +/-10% |
| Contact Form | 2 Form C (DPDT) |
| Contact Material | Silver Alloy With Gold Alloy Overlay |
| Voltage Characteristics | 2.25 (Operate) / 0.3 (Release) |
| Switching Power | 30 W, 37.5 VA |
| Switching Voltage DC | 220 V |
| Switching Voltage AC | 250 VAC |
| Switching Current | 1A |
| Contact Current Class | >10A |
| Carrying Current | 1Amps |
| Contact Resistance | 100 mOhms |
| Operation Time | Approximately 2ms |
| Release Time | Approximately 1ms |
| Insulation Resistance | 1 GOhms |
| Withstanding Voltage | 1000 VAC (1min) 1500 V Surge |