VV Thread

S
R1
R2

P

PP

Keying Shown as example

LAYOUT SHOWN AS EXAMPLE

CHARACTERISTICS

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material	: Aluminium
-Shell Plating	: Nickel
-Insulator	: Thermoplastic
-Contacts	: Copper Alloy
-Seals & Grommet	: Silicon Elastomer
-Contact Plating	: Gold over copper Alloy 0.8µm minimum
-Durability	: 500 Mating cycles
-Delivered without Souriau contacts	
-Temperature Range	: -65°C to +200°C
-Salt Spray	: 48 hours
-Mass	: 12.62 g ± 10%

Connector dimension	
Dim	**Nominal**
P	3.25±0.2
PP	4.93±0.2
R1	20.62
R2	18.26
S	26.2±0.3
V	20.83+0/-1.25
W	2.1/2.5
Z	31.5 Max
VV THREAD	M15x1-6g

SOURIAU shall not be liable for any non-conformity or damage
due to a use of the Products which does not comply with
the Specifications issued by either of the Parties or by a third party
(professional recommendation, technical notice.)

Country	Jurisdiction & Control List
FR	Not Listed

PN: 8D011F02SCL

A	14-10-2016	First Release		
ISS	DATE	Latest modification - by		MOD N°

Designed By: Date: **CUSTOMER DRAWING**

TITLE   Aluminium Receptacle 8D series

SCALE		General linear Tolerances: ±--	NPRDS / PROJECT **859**
NA			

BASIC SERIES: 8D   0   -   11   F   02   S   C   L

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE   : Standard Crimp Contact

SHELL SIZE : 11

PLATING   : F =   Nickel

Delivered W/O Contacts

ORIENTATION : C

CONTACT TYPE : SOCKET(500 Matings)

CONTACT LAYOUT : 11-02

SOURIAU   WWW.SOURIAU.COM

FORMAT **A3**	SOURIAU DRG N° 8D011F02SCL-C	SHEET 1/2

Contact Layout

.095 (2.41mm)   .095 (2.41mm)

Contacts (Insert arrangement 11-2)		
Contact position ID	Contact location	
	X-axis (mm)	Y-axis (mm)
A	+.095 (2.41)	+.000 (.00)
B	-.095 (2.41)	+.000 (.00)

Shell size	Arrangement no.	Number of contacts	Size contacts	Service rating	Contact location
11	-2	2	16	I	All

Panel Cutout

SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING

ØT
ØA

SQUARE FLANGE RECEPTACLE (TYPE 0) FRONT MOUNTING

ØT
ØAA

Dim	Nominal
ØA	20.22 min
ØAA	15.88 min
R1	20.62
ØT	3.25 ±0.13

Country	Jurisdiction & Control List
FR	Not Listed

PN: 8D011F02SCL

A	14-10-2016	First Release	
ISS	DATE	Latest modification - by	MOD N°

Designed By: Date: **CUSTOMER DRAWING**

TITLE	Aluminium Receptacle 8D series

SCALE		General linear Tolerances: ±--	NPRDS / PROJECT **859**
NA			

SOURIAU   WWW.SOURIAU.COM

FORMAT **A3**	SOURIAU DRG N° 8D011F02SCL-C	SHEET 2/2