



TABLE 1

SHELL SIZE	A THREAD	ØB MAX	ØT MIN
08	7/16 -28UNEF	18,0	6,8
10	9/16 -24UNEF	21,5	10,3
12	11/16 -24UNEF	24,5	13,1
14	13/16 -20UNEF	27,5	16,3
16	15/16 -20UNEF	32,5	19,5
18	1 1/16 -18UNEF	35,5	21,9
20	1 3/16 -18UNEF	38,5	25,1
22	1 5/16 -18UNEF	42,0	28,3
24	1 7/16 -18UNEF	45,0	31,5

TABLE 2

CODE	MATERIAL / PLATING
1-C	ALUMINIUM / ELECTROLESS NICKEL
1-B	ALUMINIUM / CADMIUM OLIVE DRAB OVER ELECTROLESS NICKEL
1-ZB	ALUMINIUM / ZINC COBALT OLIVE DRAB OVER ELECTROLESS NICKEL
1-G	ALUMINIUM / BLACK ANODISE, SULPHURIC
4-J	STAINLESS STEEL / PASSIVATE
2-Z	NICKEL ALUMINIUM BRONZE / SHOT BLAST

LIST NOT EXHAUSTIVE, SEE MATERIAL AND PLATING TABLE FOR FULL LIST

99F1-16-1-C

SERIES _____

CONNECTOR INTERFACE _____

ANGLE _____

SHELL SIZE (TABLE 1) _____

MATERIAL (TABLE 2) _____

FINISH (TABLE 2) _____

DRAWN K. WINCZURA	DATE 22/02/2012	3RD ANGLE PROJECTION NOT TO SCALE	POLAMCO LTD www.polamco.com	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP	PAGE 1	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN MILLIMETRES
SALES APPR						
DESIGN APPR K. SHEPPARD	22/02/2012	THIS DRAWING IS COPYRIGHT AND THE PROPERTY OF POLAMCO LTD. IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY.	ASSY USED ON: MIL-DTL-38999 SERIES I & II			MATERIAL
PROD APPR			TITLE:			SEE TABLE 2
QUAL APPR			GROMMET ADAPTOR			NCAGE CODE U5792
ISSUE 3	DCR 3969		PART NUMBER:			DRAWING NO: P10266
WEIGHT	GENERAL TOL LINEAR +/-0,25MM ANGULAR +/-1°	99F1 SERIES				