

## Contact insert - RC-07P1NS20000 - 1594515

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Contact insert, Number of positions: 7, Type of contact: Male connector, Screw connection

The figure shows the 6-pos. product version



### Key commercial data

Packing unit	1 PCE
GTIN	 4 046356 276047
Custom tariff number	85389099
Country of origin	GERMANY

### Technical data

#### Technical data

Insertion/withdrawal cycles mechanical	50
Direction of rotation of contact chamber numbering	Standard
Coding	N
Contact connection method	Screw connection
Type of contacts	Male connector
Number of positions	7
Contact diameter of power contacts	2 mm
Nominal current per power contact at 25°C	20 A

#### Material data

Contact material	CuZn
Contact surface	Nickel-plated, gold coating

Specifications according to DIN EN 61984:2001

# Contact insert - RC-07P1NS20000 - 1594515

## Technical data

Specifications according to DIN EN 61984:2001

Nominal / operating voltage of signal contacts	150 V
Rated surge voltage of signal contacts	2.5 kV
Surge voltage category of signal contacts	II
Pollution degree of signal contacts	3
Surge voltage category of power contacts	II
Pollution degree of power contacts	3

## Classifications

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC001121

### UNSPSC


UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404
UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404

### eCl@ss


eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312

## Drawings

Schematic diagram



Schematic diagram



## Contact insert - RC-07P1NS20000 - 1594515

Schematic diagram

