

Guaranteed compatibility when used with recommended Tripp Lite cabling. Designed specifically for use with Tripp Lite cables, such as the N820- and N821-Series cables

40/100Gb OM4 Fiber Breakout Cassette with Built-In MTP Cables, 40Gb to 4 x 10Gb, 100Gb to 4 x 25Gb, (x3) 8-Fiber OM4 MTP/MPO to (x12) LC Duplex

MODEL NUMBER: **N482-3M8L12-B**



Installs in select Tripp Lite fiber chassis to connect 12 LC duplex fiber cables with three 8-fiber MTP/MPO connections in high-density network applications.

Description

The N482-3M8L12-B OM4 Fiber Breakout Cassette works in tandem with Tripp Lite's N482-01U or N482-02U chassis to connect 12 LC duplex fiber cables with three 8-fiber MTP/MPO connections in high-density network applications. The cassette features three built-in 2-meter 8-fiber MTP cables. Color-coded magenta OM4 cables are easily distinguished from traditional aqua OM3 multimode fiber.

The cassette's modular design installs easily in the N482-01U and N482-02U chassis with no tools required. Just insert the cassette into the chassis, and screw in its retention clips to secure it. Plug LC patch cables, such as Tripp Lite's N820-01M-T cables, into the cassette using the convenient push/pull tabs. Up to five N482-3M8L12-B cassettes fit in the N482-01U 1U enclosure panel, and up to 14 cassettes fit in the N482-02U 2U sleeve. Dust tabs protect unused ports from potential damage. Guaranteed compatibility when used with recommended Tripp Lite cabling. Designed specifically for use with Tripp Lite cables, such as the N820- and N821-Series cables.

The N482-3M8L12-B complies with IEEE 802.3ae (10 GbE) and ANSI T11.2 (Fibre Channel) requirements. Supports 40 GbE internally using OM4 fiber optic cable. Base-8 Fiber compatible with both QSFP+ 40GBASE-SR4 to SFP+ 10GBASE-SR and QSFP28 100GBASE-SR4 to SFP28 25GBASE-SR connections. Ideal for QSFP fabric switches that use eight out of 12 available MTP fibers for four-lane parallel optics to 40 GB, allowing all 12 LC duplex cassette ports to be used. Maximum insertion loss of 0.35 dB falls well under the IEEE 802.3ae maximum channel loss specification of <25 dB. This cassette also supports devices of varying speeds, including 10 GB and 40 GB network equipment.

With factory-terminated connectors that reduce time and labor, the N482-3M8L12-B is made from only the finest materials to ensure fast installations and optimal performance.

Features

Elegant, Simple Solution for 40Gb to 10Gb, or 100Gb to 25Gb, LC Cable ConnectionsHigh-density

Highlights

- For use with Tripp Lite N482-01U or N482-02U chassis
- 3 magenta built-in 2-meter 8-fiber MTP multimode cables
- Guaranteed compatibility when used with recommended Tripp Lite cabling
- Designed specifically for use with Tripp Lite cables, such as the N820- and N821-Series cables
- Factory-terminated OM4 connectors
- Supports 40 GbE internally using OM4 fiber optic cable
- Base-8 Fiber compatible with both QSFP+ 40GBASE-SR4 to SFP+ 10GBASE-SR and QSFP28 100GBASE-SR4 to SFP28 25GBASE-SR connections
- Simple installation with no tools required

System Requirements

- QSFP switches that use 8-fiber per port to support 4 x LC 10 GB breakout
- Guaranteed compatibility when used with recommended Tripp Lite cabling
- Designed specifically for use with Tripp Lite cables, such as the N820- and N821-Series cables

Package Includes

- N482-3M8L12-B OM4 Fiber



fiber cassette for use with Tripp Lite N482-01U and N482-02U fiber enclosure panels
 3 magenta built-in 2-meter 8-fiber MTP multimode cables
 Connect up to 12 LC duplex fiber cables with 3 8-fiber OM4 MTP/MPO connections
 Recommended for use with QSFP fabric switches to support 4 lanes parallel to 40 GBS
 Supports 40 GbE internally using OM4 fiber optic cable
 Base-8 Fiber compatible with both QSFP+ 40GBASE-SR4 to SFP+ 10GBASE-SR and QSFP28 100GBASE-SR4 to SFP28 25GBASE-SR connections
 Guaranteed compatibility when used with recommended Tripp Lite cabling
 Designed specifically for use with Tripp Lite cables, such as the N820- and N821-Series cables
Simple Fiber Installations Save Time and Money
 Easy installation with no tools required
 Install up to 14 cassettes in N484-02U 2U chassis
 Install up to 5 cassettes in N484-01U 1U chassis
Easy to Modify, Upgrade or Expand Fiber Infrastructure By Adding or Swapping Cassettes
 Complies with IEEE 802.3ae (10 GbE) and ANSI T11.2 (Fibre Channel) requirements
 0.35 dB maximum insertion loss falls under IEEE 802.3ae maximum channel loss spec of <25 dB
 Supports devices of varying speeds, including 10 GB and 40 GB network equipment
Premium Construction for Optimal Performance
 Factory-terminated connectors reduce time and labor
 Dust caps protect unused ports

- Breakout Cassette
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332200853
PHYSICAL	
Shipping Dimensions (hwd / cm)	5.08 x 33.53 x 11.43
Shipping Dimensions (hwd / in.)	2.00 x 13.20 x 4.50
Shipping Weight (kg)	0.27
Shipping Weight (lbs.)	0.60
CONNECTIONS	
Ports	12
Side A - Connector 1	8-STRAND MTP (FEMALE)
Side B - Connector 1	LC DUPLEX (FEMALE)
FEATURES & SPECIFICATIONS	
Technology	MTP/MPO; Multimode; SFP+/QSFP+/QSFP28
SPECIAL FEATURES	
Built-in Cables	Yes
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

<https://www.tripplite.com/products/product-certification-agencies>