



## Launch Pin to Pin Contact with 0.012" Diameter Full Radius Pin with 0.159" Pin Length and Dielectric

### TECHNICAL DATA SHEET

PE1017-4

#### Configuration

Description	Launch Pin to Pin Contact
Pin Diameter, in [mm]	0.012 [0.3]
Pin Length, in [mm]	0.159 [4.04]
Contact Diameter, in [mm]	0.007 [0.18]
Tab Size, in	0.030
Contact Material and Plating	Beryllium Copper Gold
Contact Plating Specification	40 $\mu$ in minimum
Dielectric Material	PTFE

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

- Values at +25 °C, sea level

Launch Pin to Pin Contact with 0.012" Diameter Full Radius Pin with 0.159" Pin Length and Dielectric from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Launch Pin to Pin Contact with 0.012" Diameter Full Radius Pin with 0.159" Pin Length and Dielectric PE1017-4](#)


URL: <https://www.pasternack.com/hermetic-seal-solder-contact-0.011-pin-diameter-0-body-0.159-pin-pe1017-4-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE1017-4 CAD Drawing

Launch Pin to Pin Contact with 0.012" Diameter Full Radius  
Pin with 0.159" Pin Length and Dielectric

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	2/23/2021	S.PONG



## NOTES:

- FINISH (PLATING THICKNESS IN MICRO-INCHES)
  - BERYLLIUM COPPER.
  - GOLD PL.40 MIN. OVER NICKEL-PHOSPHORUS ALLOY
  - PL. 80 MIN. OVER COPPER PL. 20MIN.

UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:  
 .X = ±.2 [508]    FRACTIONS ±.1/32  
 .XX = ±.02 [51]    ±.1/32  
 .XXX = ±.005 [13]    ANGLES ± 1°

CABLE LENGTH (L), TOLERANCES:  
 L ≤ 12 [305] = +1 [25] / -0  
 12 [305] < L ≤ 60 [1524] = +2 [51] / -0  
 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0  
 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0  
 300 [7620] < L = +5% / -0

ALL DIMENSIONS SHOWN  
ARE FOR REFERENCE ONLY.

THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.

SHEET 1 OF 1

SCALE N/A

REV A

ITEM NO. PE1017-4

DRAWN BY K.DANG

CAGE CODE 53919

ITEM NO. PE1017-4

REV A

**PE PASTERNAK**  
an INFINITE brand

Pasternack Enterprises, Inc.  
P. O. Box 16759, Irvine, CA 92623.  
Phone: 1.949.261.1920 | 1.866.727.8376  
Fax: 1.949.261.7451  
Website: www.pasternack.com  
E-mail: sales@pasternack.com