



| SIGN | DATE | DESCRIPTION | APPROVER |
|------|------|-------------|----------|
| △    |      |             |          |

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Item A Terminal housing: Thermoplastic (UL94V-0)
  - Item B Terminal cover: Thermoplastic (UL94V-0)
  - Item C Female contact : Copper. Tin plated
  - Item D Wire guard : Stainless Steel
  - Item E Clamp : Steel Stamping , Zinc plated
  - Item F Handle: Steel t=1.5mm, Zinc plated
  - Item G Terminal screw: Zinc plating"-slot type,M5
  - Item H With flange screw: Zinc plating"x-slot type,M5
- Electrical: cULus
- Voltage rating: 600 V
  - Current rating: 115 A
  - Wire range:
  - Solid wire(AWG): 2-20
  - Stranded wire(AWG): 2-20
  - Torque(Lb-In): 36.5
  - Screw: M5
  - Wire strip length: 19-20mm
  - Withstanding Voltage: 2.2 KV
  - Operating temperature: -40°C to +115°C
  - APPROVAL:

**KX 04 C 1 x 2 xxxx G**

No. OF POLES \_\_\_\_\_ G: Pb<4000ppm  
 04: 4 POLES \_\_\_\_\_ 0000: "@ " Logo (Standard)  
 COLOR \_\_\_\_\_ 000A: "ANYTEK" Mark  
 Any special item by customer request.  
 please contact sales department.

0: BLACK  
 5: GREEN (RAL 6018/T)  
 6: BLUE  
 8: GREY (RAL 7035/D)

|   |                                   |                      |                      |                      |         |             |            |
|---|-----------------------------------|----------------------|----------------------|----------------------|---------|-------------|------------|
| <b>ANYTEK</b>   |                                   |                      |                      | <b>CUSTOMER COPY</b> |         |             |            |
| ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD |                                   |                      |                      |                      |         |             |            |
| TITLE   | KX 15.0mm Series (with handle) 4P |                      |                      | DWG NO.              | 8KX0002 |             |            |
| PART NO.  | KX04C1x2xxxxG                     |                      |                      | CUST NO.             |         |             |            |
| APPROVED  | CHECKED                           | DESIGNED             | DRAWN                |                      |         | Tolerance   |            |
|   |                                   | Runner<br>2011.04.25 | Runner<br>2010.05.24 |                      |         | UNIT: mm    | X. ±0.50   |
|   |                                   |                      |                      | SHEET: 01/01         |         | SCALE: NONE | X.X ±0.30  |
|   |                                   |                      |                      |                      |         | REV.: B     | X.XX ±0.10 |
|   |                                   |                      |                      |                      |         |             | X° ±1°     |