



Click [here](#) for the 3D model.

Dimensions

D	30mm +/-0.5mm
L	25mm +/-1mm
S	10mm +/-0.1mm
LL	4mm +/-1mm
F	2mm +/-0.1mm

Packaging Specifications

Packaging	Bulk, Bag
-----------	-----------

General Information

Series	PEH526
Dielectric	Aluminum Electrolytic
Description	Snap-In, Aluminum Electrolytic
RoHS	Yes
Lead	3 Pin Short
Qualifications	AEC-Q200
AEC-Q200	Yes
Component Weight	24 g
Notes	Add 0.5mm To D And 1mm To L For Sleeving.
Shelf Life	520 Weeks

Specifications

Capacitance	1,800 uF
Capacitance Tolerance	20%
Voltage DC	63 VDC
Temperature Range	-40/+125°C
Rated Temperature	125°C
Life	4000 Hrs
Resistance	76 mOhms (100Hz 20C), 45 mOhms (100kHz 20C), 29 mOhms (>=5kHz 125C)
Ripple Current	1.8 Amps (100Hz 125C), 7.7 Amps (5kHz 85C), 5.9 Amps (5kHz 105C), 2.9 Amps (5kHz 125C)
Leakage Current	1134 uA (5min 20°C)