

SIDE VIEW



TERMINAL END VIEW



Click [here](#) for the 3D model.

| Dimensions  |                |
|-------------|----------------|
| D           | 8mm +/-0.5mm   |
| L           | 11mm +1.5mm    |
| S           | 3.5mm +/-0.5mm |
| LL Negative | 15mm MIN       |
| LL Positive | 20mm MIN       |
| F           | 0.6mm NOM      |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 6000      |

| General Information |                                     |
|---------------------|-------------------------------------|
| Series              | ESK                                 |
| Dielectric          | Aluminum Electrolytic               |
| Description         | Single Ended, Aluminum Electrolytic |
| RoHS                | Yes                                 |
| Lead                | Wire Leads                          |
| AEC-Q200            | No                                  |

| Specifications          |                          |
|-------------------------|--------------------------|
| Capacitance             | 3.3 uF                   |
| Capacitance Tolerance   | 20%                      |
| Voltage DC              | 200 VDC, 250 VDC (Surge) |
| Temperature Range       | -25/+85°C                |
| Rated Temperature       | 85°C                     |
| Life                    | 2000 Hrs                 |
| Dissipation Factor      | 15% 120Hz 20C            |
| Ripple Current          | 37 mAmps (120Hz 85C)     |
| Leakage Current         | 29.8 uA (2min 20°C)      |
| Impedance Ratio at -25C | 7                        |