	T O	П	m	D	0	Ū	A		
4					<image/>	OUT SHOWN AS EXAMPLE			4
		Keying Shown as	example						
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic		Connector dimension Dim Nominal A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4		due to a use of the Specifications	ot be liable for any non-conformi of the Products which does not co issued by either of the Parties or	omply with by a third party		
N	-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum		W 2.2+0.9/-0.1 VV THREAD M15x1-6g		(professio	Country Juriso	liction & Control List Not Listed]	2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				P	N: 8D711W04SD			
	-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours-Mass: 21.05 g ± 10%			ISS DA		n - by		MOD N°	
				Designed By:	Date:	Aluminium Receptac	customer drawing		
_ _	BASIC SERIES: 8D 7 - 11 SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact	W 04 S D	ORIENTATI	SCALE NA		General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the pro SOURIAU	perty of	1
	SHELL SIZE : 11		CONTACT TYPE : SOCKET(500 Ma	atings)	AU WWW.	SOURIAU.COM	it must not be reproduc communicated without pe	ermission	
	PLATING : W = Olive drab Cadmium			: 11-04 FORMAT A3		SOURIAU DRG N° 8D711W04SD-C		SHEET 1/2	
_	H G	F	E	D	С	В	A		

Г	т	G	П	m		0	Φ			n
4	.×	Contact Layout $\downarrow \qquad \qquad$				Panel cutout JAM NUT RECEPTACLE (TYPE 7)	м со			4
	Shell Arrangement Numb size no. contained no. contained no	X-axis (mm) Y-axis (mm) +.065 (1.65) +.065 (1.65) +.065 (1.65) 065 (1.65) 065 (1.65) 065 (1.65) 065 (1.65) +.065 (1.65) 065 (1.65) +.065 (1.65) er of Size contacts rating location			Ĺ	Dim Nominal B 19.59+0/-0.	25			
ω						ØC 20.96+0.25/				3
						SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N						FR Not Listed PN: 8D711W04SD				2
					A 01-10-201 ISS DATE	L6 FIRST Release			MOD N°	
					Designed By:	Date:		CUSTOMER DRAWING		
					TITLE	Alun	ninium Receptacle	e 8D series		
-					SCALE NA	Genera Tolera ±	ances: 	NPRDS / PROJECT 859 This document is the proper	rty of	1
					SOURIAL	SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission				
					FORMAT A3		RIAU DRG N°		SHEET 2/2	
L	Н	G	F	E		C C	11W04SD-C B	A	<i>L L</i>	J
					/					