

Specification Sheet

Part Number: 300-73608



Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, .75" Supp/.38" Recov Dia, PO-X, Black, 200ft/reel

Article Number	300-73608
Type	TCN20-19.1/9.5
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Tubing is 2:1, thin wall and self extinguishing providing good resistance to common fluids and solvents.• Low shrink temperature gives excellent physical and electrical performance.• Available in multiple diameters and lengths offering several options to fit specific needs.
Quantity Per	box

Product Description

TCN20 Heat Shrink is a general purpose, thin wall tubing used to protect electrical and mechanical wiring. Polyolefin material is self extinguishing and resistant against common fluids and solvents. The low shrink temperature and mechanical strength make this tubing widely used in the electric and electronics industry. Available in a wide range of diameters up to 2.0 (50.8mm) and multiple lengths. TCN20 Heat Shrink is UL224 125 °C 600V VW-1 and RoHS.

Short Description	Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, .75" Supp/.38" Recov Dia, PO-X, Black, 200ft/reel
Global Part Name	TCN20-19.1/9.5-PO-X-BK
Length L (Imperial)	200.0
Length L (Metric)	61.0
Variant	Thin-Wall
Nominal Diameter (Imperial)	3/4
Nominal Diameter (Metric)	19.1
Wall Thickness WT (Imperial)	.031
Wall Thickness WT (Metric)	0.80
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
Flammability	Self-Extinguishing
Halogen free	No
Operating Temperature (Metric)	-67°F to +257°F (-55°C to +125°C)
Reach Complaint(Article 33)	Yes

ROHS Complaint	Yes
Certification/Specification WEB	UL 224 125 °C 600V VW-1 CSA C22.2 no. 198.1-06
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	200
Package Quantity (Metric)	61
Customs Number	3926909987