

Label - MM-EML (EX24)R C1 WH/BK - 0803973

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Label, continuous, cassette, white with black imprint, mounting type: adhesive, can be marked with THERMOFOX

Product Description

The MM-EML... polyamide self-adhesive labels are available as continuous media for equipment marking.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 212494
GTIN	4055626212494

Technical data

Dimensions

Length (b)	8000 mm
Width (a)	24 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 149 °C
---------------------------------	-------------------

General

Color	white
Components	free from silicone, halogen, and cadmium
Material	Polyester
RoHS compliant	Yes
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Adhesive	Acrylic
Printability	Thermal transfer
Device	0803984 THERMOFOX
Marking mounting type	adhesive

Label - MM-EML (EX24)R C1 WH/BK - 0803973

Technical data

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>