


Notes:

1. Only RoHS Compliant Processes and Materials used for this assembly.
2. Marking to Contain "ConductRF", Part No. & WK/YR Date Code, Black Text.
3. 100% Sweep Tested to Max Frequency w. Factory Stored Hi-Point Data

ConductRF(Wk/Yr)
LSA29-N1N3-XXX

Marker Example




ConductRF # (XXX)	Length	Insertion Loss(dB) - Typ	
		18GHz	
S12	12"	1.03	
S16	16"	1.26	
S18	18"	1.38	
S24	24"	1.73	
S36	36"	2.43	
S48	48"	3.13	
S55	55"	3.54	
S60	60"	3.84	
VSWR Typ.		1.40:1	

Part No. Configurator - XXX

FXX = Length in Feet (eg F03=3ft)
SXX = Length in Inches (eg S18=18")
XXM = Length in Meters (eg 2M5=2.5m)
CXX = Length in CM (eg C50=50cm)

5	Label	Shrink Tube	White
4	Strain Relief	Shrink Tube	Black
3	Flexible Spiral Coax	A29SS	Blue FEP
2	Type-N Bulkhead	N5F31C-A29N01	Nickel
1	Type-N Str. Male	N5M17D-A29N01	Nickel
ITEM	DESCRIPTION	MATERIALS	FINISH

REV.	DESCRIPTION	ECN	DRAWN	DATE	Customer DWG	Title: Low Loss 0.141" Flexible N M to N BKHD - 18GHz			
2	Updated Table & Graphics		DG	02/07/20	Remarks:	Originated: 08/18/14	Conduct RF sales@ConductRF.com Tel: +1 978 374 6840	Range: LSA	
1	Pre-Release		DG	12/17/14		Dwg Ref: LSA29-N1N3			
					Length Tolerances: ≤24" = ±0.25" >24" = ± 1%	Checked: JW	Approved: PL	Rev: 2	Part No: LSA29-N1N3-XXX
REVISION HISTORY									