



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +200°C
- Salt Spray : 2000 hours
- Mass : 49.9 g ± 10%

| Connector dimension | |
|---------------------|----------|
| Dim | Nominal |
| ØS | 44.9 Max |
| Z' | 31.5 Max |
| VV THREAD | M34x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D523M21SEL


| | | | |
|--------------|------------|--------------------------|-------------------------|
| A | 06-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |

| | | | |
|--------------|---------------------------------|--|--|
| TITLE | Composite Plug 8D series | | |
|--------------|---------------------------------|--|--|

| | | | |
|-------|--|--------------------------------|-----------------|
| SCALE | | General linear Tolerances: ±-- | NPRDS / PROJECT |
| NA | | | 859 |

| | | |
|----------------|------------------------|---|
| SOURIAU | WWW.SOURIAU.COM | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
|----------------|------------------------|---|

| | | |
|-----------|-------------------------------------|------------|
| FORMAT | SOURIAU DRG N° 8D523M21SEL-C | SHEET |
| A3 | | 1/2 |



Contact Layout



| Contacts (Insert arrangement 23-21) | | | | | |
|--|---------------|---------------|---------------------|--------------|--------------|
| Contact position ID | Location | | Contact position ID | Location | |
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +128 (3.25) | +385 (9.78) | M | -289 (7.34) | +285 (7.24) |
| B | +289 (7.34) | +285 (7.24) | N | -128 (3.25) | +385 (9.78) |
| C | +386 (9.80) | +123 (3.12) | P | +000 (0.00) | +245 (6.22) |
| D | +400 (10.16) | -.065 (1.65) | R | +160 (4.06) | +146 (3.71) |
| E | +328 (8.33) | -.239 (6.07) | S | +214 (5.44) | -.035 (0.89) |
| F | +183 (4.65) | -.362 (9.19) | T | +.094 (2.39) | -.194 (4.93) |
| G | +000 (0.00) | -.406 (10.31) | U | -.094 (2.39) | -.194 (4.93) |
| H | -.183 (4.65) | -.362 (9.19) | V | -.214 (5.44) | -.035 (0.89) |
| J | -.328 (8.33) | -.239 (6.07) | W | -.160 (4.06) | +146 (3.71) |
| K | -.400 (10.16) | -.065 (1.65) | X | +000 (0.00) | +000 (0.00) |
| L | -.386 (9.80) | +123 (3.12) | --- | --- | --- |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 23 | -21 | 21 | 16 | II | All | MS20056-21 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D523M21SEL

| | | | |
|----------------|-------------------------------------|----------------------------|---|
| A | 06-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Composite Plug 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D523M21SEL-C | | SHEET 2/2 |