

Note: The cloning function will not work if the U339-002 is connected to a computer or any other source via a USB cable.

## USB 3.0 SuperSpeed to Dual SATA External Hard Drive Docking Station with Cloning for 2.5 in./3.5 in. HDD

MODEL NUMBER: **U339-002**



SuperSpeed ( 5Gbps ) Data Transfer over USB 3.0

### Description

Tripp Lites U339-002 USB 3.0 SuperSpeed to Dual SATA External Hard Drive Docking Station allows two SATA 2.5in or 3.5in hard drives (HDD) or solid state drives (SSD) to be connected simultaneously to a computer through USB. Supports 2.5" and 3.5" drives up to 6TB. Will support larger capacity drives as they become available. Off-line cloning allows hard drive duplication without being connected to a computer.

Utilizing SuperSpeed USB 3.0, this docking station provides data transfer rates of up to 5 Gbps, but is also backward compatible with USB 2.0 systems (data transfer rates up to 480 Mbps).

### Features

- Dual SATA docking station enables the connection of two 2.5" or 3.5" hard drives via a computer's USB port.
- Easy set-up eliminates the need for time-consuming internal installation and facilitates access to a hard drive's contents.
- Offline cloning functionality allows hard drive duplication with the touch of a button – a host computer connection is not needed.
- An LED progress bar displays cloning status.
- Supports USB 3.0 connections with data transfer rates up to 5Gbps.
- Compliant with SATA HDD or SSD drives up to SATA III
- Backwards compatible with USB 2.0 and USB 1.1 standards.
- Docking functionality compatible with Windows, MAC, and Linux systems

## Specifications

### Highlights

- Read and Write to two drives simultaneously
- Supports 2.5" or 3.5" SATA drives up to 6TB
- Docking functionality compatible with Windows, MAC, and Linux systems

### System Requirements

- (x2) 2.5" or 3.5" SATA Hard Drive.
- Computer with an available USB port. **Note:** A USB 3.0 port is required to achieve maximum transfer speeds up to 5Gbps. Cloning functionality will not work if the U339-002 is connected to a computer.
- Docking functionality compatible with Windows, Mac and Linux systems.
- Offline clone copies data from the master drive to the slave drive, leaving the remaining data unallocated. Windows computers will be able to reallocate the remaining data, whereas Mac and Linux computers will not.

### Package Includes

- U339-002 USB 3.0 SuperSpeed to Dual SATA External Hard Drive Docking Station
- 2.5-ft. USB 3.0 Device Cable
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 1.5A; Output:12V, 3A)
- Owner's Manual

| <b>OVERVIEW</b>                                |   |
|--|---|
| UPC Code                                       | 037332181299  |
| Technology                                     | SATA/eSATA  |
| <b>INPUT</b>                                   |   |
| Voltage Compatibility (VAC)                    | 100; 110; 120; 127; 200; 208; 220; 230; 240         |
| Bus Powered                                    | No  |
| <b>POWER</b>                                   |   |
| Power Source Type                              | AC Adapter  |
| External Power Supply Plug(s)                  | NEMA 1-15P North America                            |
| External Power Supply Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 1.5A                           |
| External Power Supply Output Specs (V / A)     | 12V / 3A  |
| External Power Supply Cord Length (ft.)        | 4.9   |
| External Power Supply Cord Length (m.)         | 1.5   |
| AC Adapter                                     | Input: 100-240V, 50/60Hz, 1.5A; Output: 12V, 3A     |
| DC Barrel Plug                                 | OD: 5.5 x 2.1 x 10mm, Positive Pin, Negative Sleeve |
| Power Consumption (Watts)                      | 36  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>   |   |
| LED Indicators                                 | Red (Read, Write, Power); Blue (Clone)              |
| <b>PHYSICAL</b>                                |   |
| Color  | Black   |
| Material of Construction                       | ABS   |
| Shipping Dimensions (hwd / in.)                | 2.70 x 6.30 x 8.00                                  |
| Shipping Dimensions (hwd / cm)                 | 6.86 x 16.00 x 20.32                                |
| Shipping Weight (lbs.)                         | 1.70  |
| Shipping Weight (kg)                           | 0.77  |
| Unit Dimensions (hwd / in.)                    | 0.000 x 0.000 x 0.000                               |
| Unit Dimensions (hwd / cm)                     | 6.2 x 15.3 x 11.1                                   |
| Unit Packaging Type                            | Box   |
| Unit Weight (lbs.)                             | 0.9   |
| Unit Weight (kg)                               | 0.41  |

| <b>ENVIRONMENTAL</b>                 |  |
|--------------------------------------|--|
| Operating Temperature Range          | 50 to 122 F (10 to 50 C)                             |
| Storage Temperature Range            | 32 to 149 F (0 to 65 C)                              |
| Relative Humidity                    | 10% to 80% RH, Non-Condensing                        |
| BTUs                                 | 122.8 BTU/Hr   |
| <b>CONNECTIONS</b>                   |  |
| Number of Ports                      | 2  |
| Side A - Connector 1                 | USB 3.0 A (MALE)                                     |
| Side B - Connector 1                 | (2) 22 PIN SATA + POWER (FEMALE)                     |
| Connector Plating                    | Nickel   |
| <b>FEATURES &amp; SPECIFICATIONS</b> |  |
| USB Specification                    | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps) |
| Driver Required                      | No   |
| UASP Support                         | Yes  |
| IP68 Rated                           | No   |
| IP20 Rated                           | No   |
| <b>STANDARDS &amp; COMPLIANCE</b>    |  |
| External Power Supply Certifications | FCC; UL; cUL; RoHS                                   |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA)                  |
| <b>WARRANTY &amp; SUPPORT</b>        |  |
| Product Warranty Period (Worldwide)  | 3-year limited warranty                              |