



Electrical Characteristics

Nominal Impedance: Non Constant
 Frequency Range: DC to 300 MHz
 Operating Voltage (rms): 500 V maximum at sea level
 Dielectric Withstand Voltage (rms): 1500 V maximum at sea level
 Insulation Resistance: 500 megohms minimum

Mechanical Characteristics

Mating Cycles: 500 cycles minimum

Environmental Characteristics

Temperature Range: -55 °C to +85 °C

PART	DESCRIPTION
1	Body Brass, nickel plated
2	Nut Brass, nickel plated
3	Dielectric POM
4	Contact Brass, nickel plated

CAD Issue	SN	2	25 Nov 02
First Issue	AT	1	30 Jun 00
DESCRIPTION OF REVISION	APPVD	ISS	DATE



Cinch Connectivity Solutions
 7-13 Russel Way,
 Widford Industrial Estate,
 Chelmsford, Essex,
 CM1 3AA, UK.
 Tel: +44 (0) 1245 359515
 Fax: +44 (0) 1245 358938

SCALE: Not To Scale	DRAWN BY:	S Nash
DIMENSIONS: mm	CHECKED BY:	
TOLERANCES: ± 0.2mm unless otherwise stated	APPROVED BY:	
	DATE:	25 Nov 02

TITLE:
**UHF Bulkhead Jack to
 Jack Adaptor**

PART NUMBER:
VUA105
 PAGE: 1 of 1