



**SS** Stainless Steel

**2 Type**

- A** Without lock nut
- AK** With lock nut

**Metric table**

Dimensions in: millimeters - inches

d <sub>1</sub> Pin -0.02 -0.05 Bore H7	b	d <sub>2</sub> Thread	d <sub>3</sub>	e ≈	l <sub>1</sub>	l <sub>2</sub> ± 0.5	l <sub>3</sub> - 0.15	l <sub>4</sub>	l <sub>5</sub>	A/F	Spring load ≈				Axial load
											Steel Initial	End	Stainless steel Initial	End	
6 .24	4 .16	M 12 x 1.5	25 .98	19.6 .77	45 1.77	6 .24	10 .39	5 .20	3 .12	17 .67	11 N 2.47 lbf	28 N 6.29 lbf	9 N 2.02 lbf	25 N 5.62 lbf	400 N 89.92 lbf
8 .31	4.5 .18	M 16 x 1.5	31 1.22	21.9 .86	54 2.13	8 .31	12 .47	6 .24	3 .12	19 .75	15 N 3.37 lbf	29 N 6.52 lbf	13 N 2.92 lbf	26 N 5.85 lbf	500 N 112 lbf

**Specification**

- Threaded body
  - Steel, blackened finish **ST**
  - Plunger pin hardened
  - Thin hexagon nut GN 909
- Stainless steel **NI**
  - European Standard No. 1.4305 (AISI 303)
  - Plunger pin chemically nickel plated
  - Thin hexagon nut GN 909.5
- Knob
  - Plastic
  - Technopolymer (Polyamide PA)
  - Temperature resistant up to 230 °F (110 °C)
  - Black, matte finish
  - Not removable
- Lock nut
  - Thin hexagon nut GN 909 / GN 909.5
  - Steel, blackened finish
  - Stainless steel
  - European Standard No. 1.4305 (AISI 303)
- RoHS compliant

**Information**

GN 607 short indexing plungers are standard units used for a wide range of indexing applications where the threaded body needs to be reduced to a minimum.

The extremely thin GN 909 / GN 909.5 lock nuts increase the mounting options.

**see also...**

- *List of Indexing Plunger Types*
- *Locating Bushings GN 412.2 / GN 412.4*
- *Locating Bushings with Cone GN 412.3 / GN 412.5*
- *Spacer Bushings GN 609.5 (to Limit the Thread Length)*

How to order <b>GN607-8-AK-ST</b>	<b>1</b> Pin diameter d <sub>1</sub>
	<b>2</b> Type
	<b>3</b> Material