samtec


SS–132–G–2


ESD–115–TT–05

(2.54 mm) .100"

SS, SD, ESD, ESS, HSS SERIES

PRECISION MACHINED SOCKET STRIPS

Mates with:
TS, TD, HTS, BBS, BBD, BBL, BDL, BHS

SPECIFICATIONS

For complete specifications see www.samtec.com?SS, www.samtec.com?ESS, www.samtec.com?SD, www.samtec.com?ESD or www.samtec.com?HSS

Insulator Material:
SS, SD, ESS, ESD= Black G.F. Polyester
HSS= Black Liquid Crystal Polymer
Contact:
BeCu
Shell:
Brass except Style 5A Phosphor Bronze
Plating:
Au over 50 µ" (1.27 µm) Ni or Sn over 50 µ" (1.27 µm) Ni
Operating Temp Range:
-55 °C to +125 °C
Lead Size Range:
(0.38 mm to 0.56 mm) .015" to .022" DIA and most IC leads
RoHS Compliant:
Yes
Lead-Free Solderable:
Wave only

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality

FILE NO. E111594

Note:
Some lengths, styles and options are non-standard, non-returnable.

TYPE STRIP	1	NO. PINS PER ROW	PLATING OPTION	LEAD STYLE	OPTION	OTHER OPTION

01 thru 32
= SS, ESS Series

01 thru 36
= HSS, SD & ESD Series

SS
= Standard Single Row Socket

HSS
= High Temp Single Row Socket

ESS
= Elevated Single Row Socket

Styles –5A & –05 socket heads not countersunk.



SD
= Standard Double Row Socket

ESD
= Elevated Double Row Socket

Style –5A not available.
Styles –5A & –05 socket heads not countersunk.



–S
= 10 µ" (0.25 µm) Gold contact, Tin shell (Styles 2 & 22 only)

–T
= 30 µ" (0.76 µm) Gold contact, Tin shell

–G
= 30 µ" (0.76 µm) Gold contact, 10 µ" (0.25 µm) Gold shell

–TT
= Tin contact and shell (Styles 1, 2, 4, and 05 except LIF N/A)

LIF= Low Insertion Force

– L = Locking Socket

Add **–L** suffix for locking lead socket in end positions. Requires **Style -2** or **-22** and .035" ± .003 DIA board hole.



Requires -T Plating Option

– N
= Non Flush



N/A Style –5A

ALSO AVAILABLE
(MOQ Required)

- Locking lead option on ESS and ESD series

–1A, –1B or –1C
For LIF specify –21A, –21B or –21C
(SS, HSS, SD)



LEAD STYLE	Y
–1A or –21A	(9.14) .360
–1B or –21B	(12.95) .510
–1C or –21C	(6.60) .260

–2, –22*,–5A, or –38*
*For LIF specify –22 or –38 (SS, HSS, SD)



LEAD STYLE	X DIA	Y	Z
–2 or –22	(0.51) .020	(3.18) .125	(7.62) .300
–38	(0.51) .020	(4.57) .180	(8.89) .350
–5A	(0.89) .035	(12.95) .510	(17.86) .703

Locking lead available. See OPTION.

–03, –04, –05
For LIF specify –23
(ESS, ESD)



LEAD STYLE	A	B	C
–05	(17.86) .703	(13.46) .530	(4.39) .173
–03 or –23	(11.51) .453	(8.38) .330	(3.12) .123
–04	(14.05) .553	(10.92) .430	(3.12) .123

Due to technical progress, all designs, specifications and components are subject to change without notice.

All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.