

6

5

4

3

2

1

PART NUMBER	ENGINEERING NO.	LENGTH ± TOLERANCE
1300610073	103007A46M020	6' 6.74' +3.50'/-0' [2M +88.9/-0 mm]

AUX VIEW
SCALE 1:4

NOTES:

- 1) MATERIAL: SEE TABLE
- 2) FINISHES: SEE TABLE
- 3) WRAP LABEL IS MARKED WITH P/N, DATE CODE, VOLTAGE & AMPERAGE
- 4) ELECTRICAL DATA:
INLINE CORDSET
MALE A-SIZE WITH FLYING LEADS
14AWG UNSHIELDED
POLES: 3
MAX. VOLTAGE: 600V
MAX. CURRENT 15A
PROTECTION IP67
TEMPERATURE RANGE: -20°C TO 90°C
- 5) PACKAGING:
CABLE ASSEMBLIES ARE BAGGED SEPERATELY
IN POLY BAGS WITH BAR CODE LABEL ATTACHED
TO OUTSIDE OF BAG.
- 6) ASSEMBLY IS RoHS COMPLIANT.
- 7) CERTIFICATION:
UL2237, FILE NO. E258922

P1

GREEN/YELLOW	1
BLACK	2
WHITE	3

WIRING DIAGRAM

FACE VIEW
MALE

ITEM	QTY	DESCRIPTION	MATERIAL	FINISH
7	1	DANGER LABEL	VINYL	BLACK
6	A/R	MOLDING COMPOUND	PVC	GRAY
5	1	WRAP LABEL	VINYL	YELLOW
4	1	MALE COUPLING NUT	ZINC ALLOY	BLACK E-COAT
3	3	PIN CONTACT	BRASS	GOLD PLATE
2	1	3P MALE INSERT	PVC	BLACK
1	SEE TABLE	#14/3 CABLE	PVC JACKET	GRAY

SD RELEASE EC NO: WNA2010-0426 DRWN: YOU 2010/01/13 CHKD: BWOODMAN APPR: JFMURPHY 2010/01/20	QUALITY SYMBOLS
	▽=0
	▽C=0
	REV

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm INCH
4 PLACES	±--- ±---
3 PLACES	±--- ±0.05
2 PLACES	±0.13 ±0.10
1 PLACE	±0.25 ±0.20
ANGULAR ±1/2°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE	
INCH/MM	
DRAWN BY	DATE
CHECKED BY	DATE
APPROVED BY	DATE
JFMURPHY	2010/01/20
MATERIAL NO.	
SEE CHART	
SIZE	
A	

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
1:2	INCH	☉
TITLE		
MINI-CHANGE BRAD POWER 3P MALE 90 DEGREE #14/3 AWG PVC DROP CABLE		
MOLEX INCORPORATED		
DOCUMENT NO.		SHEET NO.
SD-130061-010		1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

6

5

4

3

2

1