

## Specification Sheet

Part Number: 151-01310



Fir Tree demonstrates easy insertion with high extraction resistance in 65 +/- 0.4 mm hole

C-clip design allows for multiple uses, from hoses and tubes to harnesses and cables

**Article Number**

151-01310

**Type**

DUALFT6DOCK

**Color**

Black (BK)

**Quantity Per**

carton

**Product Description**

HellermannTyton connector clips for oval holes are mounted simply by pushing them onto the corresponding clip. The clips provide a wide range of mounting options with anti-rattle and anti-rotation features. The fir tree locks into place when inserted into the hole palpably and ensures a secure fixing at all times. Dual routing clip provides a secure fit for two routings between 12 - 15 mm diameter.

**Short Description**

Dual FT6 Docking Clip, 12-15mm with 6.5mm Fir Tree, PA66HIRHSUV, Black, 2000/pkg

**Global Part Name**

DUALFT6DOCK-PA66HIRHSUV-BK

**Length L (Imperial)**

2.04

**Length L (Metric)**

51.8

**Fixation Method**

Fir Tree

**Width W (Imperial)**

0.66

**Width W (Metric)**

16.66

**Height H (Imperial)**

1.36

**Height H (Metric)**

34.63

**Nominal Diameter (Metric)**

15.5

**Panel Thickness Min (Imperial)**

0.02

**Panel Thickness Max (Imperial)**

0.24

**Panel Thickness Min (Metric)**

0.6

**Panel Thickness Max (Metric)**

6.0

**Mounting Hole Diameter D (Imperial)**

0.26

**Mounting Hole Diameter D (Metric)**

6.5 mm

**Mounting Hole Diameter D Max (Metric)**

6.9

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	2000
<b>Package Quantity (Metric)</b>	2000
<b>Customs Number</b>	3926909988