

## Specification Sheet

Part Number: 156-00092



**Article Number**

156-00092

**Type**

T50IFT10

**Color**

Black (BK)

**Features & Benefits**

- Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.
- Fir tree provides low insertion effort yet demonstrates high extraction resistance.
- Disc feature prevents rattling in high-vibration applications and protects against debris ingress.

**Quantity Per**

bag

**Product Description**

HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

**Short Description**

2-Piece Cable Tie/Fir Tree Mount, 12.0"L, .38"-.39" Mounting Hole, 50lb, PA66HS, Black, 500/pkg

Global Part Name

T50IFT10-PA66HS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

12.0

Length L (Metric)

305.0

Fixation Method

Fir Tree

Identification Plate Position

none

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.16

Bundle Diameter Min (Metric)

4.0

Bundle Diameter Max (Imperial)

3.4

Bundle Diameter Max (Metric)

81.0

Height H (Imperial)

.05

Height H (Metric)

1.20

<b>Panel Thickness Min(Imperial)</b>	0.031
<b>Panel Thickness Max(Imperial)</b>	0.197
<b>Panel Thickness Min (Metric)</b>	0.8
<b>Panel Thickness Max (Metric)</b>	5.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.38 - 0.39
<b>Mounting Hole Diameter D (Metric)</b>	9.7 - 10.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.38
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.39
<b>Mounting Hole Diameter D Max (Metric)</b>	10.0
<b>Disc Diameter(Metric)</b>	18.0
<b>Disc Diameter (Imperial)</b>	0.7
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Complaint</b>	Yes

**Package Quantity(Imperial)**

500

**Package Quantity (Metric)**

500

**Customs Number**

3926909988