



## PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 25/4/2022  
MODIFICATION / REVISION DATE: 25/4/2022

### DK-1611-100/B MODULAR CABLE

CHANGE NOTIFICATION: PCN 20220425\_DK-1611-100/B

DESCRIPTION OF CHANGES: CHANGE OF DATA SHEET  
CHANGE OF DATA SHEET  
New Draw.-No. ASS\_7510\_CAreV01

REASON FOR CHANGE: CHANGE OF PRODUCT LOCATION  
CHANGE OF PRODUCT LOCATION

KEY CHARACTERISTICS OF CHANGE: Details see page 3

PRODUCTS AFFECTED: DK-1611-100/B

DATE OF CHANGE AND IMPLEMENTATION: CHANGE: WEEK 18 / YEAR 2022  
IMPLEMENTATION: 25/4/2022

RESPONSE: NO RESPONSE TO THIS NOTIFICATION IS REQUIRED





Auf dem Schüffel 1  
 D-58513 Lüdenscheid  
 Tel.: +49-2351 - 554-200  
 Fax: +49 (2351) 554-861  
 info@assmann-wsw.com  
 www.assmann-wsw.com

## PRODUCT CHANGE NOTIFICATION (PCN)

ISSUE DATE: 25/4/2022  
 MODIFICATION / REVISION DATE: 25/4/2022

DK-1611-100/B	OLD VERSION	DK-1611-100/B	NEW VERSION																				
Appearance		Appearance																					
BOM	<p><b>Material:</b></p> <ul style="list-style-type: none"> <li>Conductor: 24AWG 7*0.19±0.015mm</li> <li>Conductor Insulation color coding: (1) White/Orange, (1) Orange, (1) White/Green, (1) Green, (1) Blue, (1) White/Blue, (1) White/Brown, (1) Brown</li> <li>Cable jacket printing: DIGITUS Cat6 U-UTP PATCH CORD ISO/IEC 11801 &amp; TIA/EIA 568-B.2-1 24AWGx4p CM(UL) C(UL)</li> <li>Wiring T568B Color</li> <li>P1 &amp; P2 Contact plug: RJ45 8P8C 3μ pc UL 94V-2</li> </ul>	BOM	<table border="1"> <tbody> <tr> <td>①</td> <td>△</td> <td>Molding PVC</td> <td>2</td> <td>Molding PVC 65P</td> </tr> <tr> <td>①</td> <td>△</td> <td>RJ45 CONN</td> <td>2</td> <td>RJ45 8P8C, contacts 3u" gold-plated Un-shielded PC UL94V-2</td> </tr> <tr> <td>①</td> <td>△</td> <td>CABLE</td> <td>1</td> <td>CAT 5E U/UTP(24AWGx1PR)*4+PVC Jacket OD:5.6±0.3mm</td> </tr> <tr> <td>NO.</td> <td></td> <td>NAME.</td> <td>QTY</td> <td>SPECIFICATION</td> </tr> </tbody> </table>	①	△	Molding PVC	2	Molding PVC 65P	①	△	RJ45 CONN	2	RJ45 8P8C, contacts 3u" gold-plated Un-shielded PC UL94V-2	①	△	CABLE	1	CAT 5E U/UTP(24AWGx1PR)*4+PVC Jacket OD:5.6±0.3mm	NO.		NAME.	QTY	SPECIFICATION
①	△	Molding PVC	2	Molding PVC 65P																			
①	△	RJ45 CONN	2	RJ45 8P8C, contacts 3u" gold-plated Un-shielded PC UL94V-2																			
①	△	CABLE	1	CAT 5E U/UTP(24AWGx1PR)*4+PVC Jacket OD:5.6±0.3mm																			
NO.		NAME.	QTY	SPECIFICATION																			
FOR DETAIL, PLEASE TAKE ATTACHED NEW DRAWING: FOR REFERENCE																							

**PCN REVISION HISTORY:**

DATE OF REVISION: 25/4/2022

REVISION NUMBER: 00

page 3/

