

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	08DEC2015	DW	CW
	A1	ECR-17-009384	25DEC2017	RL	CW

ASSEMBLY STATE OF THE PRODUCT, FOR REFERENCE

产品装配状态, 供参考

M3 SCREW, RECOMMENDED
TIGHTENING TORQUE 0.5 Nm
M3螺丝, 推荐锁紧力矩 0.5 Nm

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 50V
RATED CURRENT: 5A
RATED IMPULSE VOLTAGE: 0.8KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
WIRE RANGE: 0.08-0.52 mm² (28-20 AWG)
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20700X10XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 50V
额定电流: 5A
额定脉冲电压: 0.8KV
污染等级: 3
阻燃等级: UL94V-0
接线范围: 0.08-0.52 mm² (28-20 AWG)
接线类型: 冷压接
- 端子需要单独订购.
(订货号参考图面: T20700X10XX000)

FOR Ø 6-9.5mm CABLE
用于直径Ø 6-9.5mm 电缆线

FOR Ø 3-6mm CABLE
用于直径Ø 3-6mm 电缆线

T2580081154-000	PIN-Q3-M	QUINTAX MALE CONTACT 8-POS QUINTAX 8-POS公针
-----------------	----------	---

PART NUMBER
料号

PART DESCRIPTION
描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-
MATERIAL	FINISH
-	-
-	-

DWN 08DEC2015

David Wang

CHK 08DEC2015

Chris Wang

APVD 08DEC2015

Xiang Xu

PRODUCT SPEC

108-137067

APPLICATION SPEC

114-137067

WEIGHT

-

NAME
QUINTAX MALE CONTACT 8-POS
PIN-Q3-M

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
------	-----------	------------	---------------

A3	00779	©-T2580081154000	-
----	-------	------------------	---

Customer Drawing	SCALE 2:1	SHEET 1 OF 1	REV A1
------------------	-----------	--------------	--------

TE Connectivity

1470-19 (3/13)