


Data sheet | Item number: 706-3340/403-300

System cable; for Schneider Modicon M340; 8 analog inputs (voltage);

Length: 3 m; Conductor cross-section: 0.25 mm<sup>2</sup>

[www.wago.com/706-3340/403-300](http://www.wago.com/706-3340/403-300)



**i** Picture differs from the item.

Color coding acc. to DIN VDE 47100	25 poles Sub-D connector		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	IN/OUT0.0	3	VI0
Brown	2	IN/OUT0.1	2	Com0
Green	3	IN/OUT0.2	4	VI1
Yellow	4	IN/OUT0.3	5	Com1
Grey	5	IN/OUT0.4	9	VI2
Pink	6	IN/OUT0.5	8	Com2
Blue	7	IN/OUT0.6	10	VI3
Red	8	IN/OUT0.7	11	Com3
Black	9	IN/OUT1.0	17	VI4
Violet	10	IN/OUT1.1	16	Com4
Grey-Pink	11	IN/OUT1.2	18	VI5
Red-Blue	12	IN/OUT1.3	19	Com5
White-Green	13	IN/OUT1.4	23	VI6
Brown-Green	14	IN/OUT1.5	22	Com6
White-Yellow	15	IN/OUT1.6	24	VI7
Yellow-Brown	16	IN/OUT1.7	25	Com7
White-Grey	17	+24V	nc	nc
Grey-Brown	18	0V	nc	nc
White-Pink	19	+24V	nc	nc
Pink-Brown	20	0V	nc	nc
White-Blue	21	nc	nc	nc
Brown-Blue	22	nc	nc	nc
White-Red	23	nc	nc	nc
Brown-Red	24	1	nc	nc
White-Black	25	2	nc	nc
Shield	Connected to Sub-D			

**Data  
Notes**

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.

## Electrical data

Inputs/outputs	8 analog inputs; voltage
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

## Compatibility

### Schneider

Schneider Modicon M340	BMX AMI 0800 BMX AMI 0810
------------------------	------------------------------

## Connection data

Cable type	LIYCY
Color code	per DIN VDE 47100

### Connection 1

Connector	D-subminiature female connector
Pole number 1	25
Connection type 1	System

### Connection 2

Connector 2	Schneider BMXFTB2020
Pole number 2	28
Connection type 2	System

## Physical data

Cable length	3 m
--------------	-----

## Material Data

Weight	488 g
--------	-------

## Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Subject to changes. Please also observe the further product documentation!



## Commercial data

ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	FR
GTIN	4055143450676
Customs tariff number	85444290900

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Downloads

### Documentation

#### System Description

WAGO System Wiring, Selection Guide	pdf	Download
This guide will help you select the appropriate interface modules and system cables for the controller you are using.	545.9 kB	

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 706-3340/403-300	URL	Download
System cable; for Schneider Modicon M340; 8 analog inputs (voltage); Length: 3 m; Conductor cross-section: 0.25 mm <sup>2</sup>		

## Installation Notes

Subject to changes. Please also observe the further product documentation!