

Safety Data Sheet
To comply with 29CFR 1910.1200
OSHA's Hazard Communication Standard

Fast Chip Part Numbers: FASTCHIP4.5-LF, FASTCHIP8-LF, FASTCHIP16-LF, FASTCHIP32-LF, SMDKIT4.5-LF, SMDKIT-LF

Tin/Bismuth/Indium Alloys

Created on 1/9/2019

1. PRODUCT AND COMPANY INFORMATION

SRA Soldering Products
24 Walpole Park South
STE 10
Walpole, MA 02081

Emergency Telephone: 1-800-535-5053 (INFOTRAC)
Telephone: 508-668-6044

2. HAZARD IDENTIFICATION

GHS Classification:

Warning



GHS Label Elements:

H Codes: H302,
Harmful if swallowed

P Codes:

P264, 270, 281, 301+312, 501, 312, 271, 301+312, 405, 201, 202, 314, 308+313

Do not handle until all safety precautions have been read & understood. Do not Get in eyes, on skin, or on clothing. Use in well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation use respiratory protection. Do not eat, drink, or smoke when using this product. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call POSION CENTER/Doctor. Get medical advice/attention if you feel unwell. Wash thoroughly after use. Dispose of contents/container in accordance with local/regional/national/international regulations for disposal. Keep out of reach of children. Read label and SDS prior to use.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	CAS #	OSHA TWA	ACIGH TWA	Other limits	%
Tin	7440-31-5	2mg/M3	2mg/M3	NE	20-40
Bismuth	7440-69-9	NE	NE	NE	50-70
Indium	7440-74-6	0.1mg/M3	0.1mg/M3	NE	2-20

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200.
An ingredient marked with an asterisk(*) is also listed in 29CFR 1910.1200(0) #4 as a known or suspected cancer hazard.

+ denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (section 313)

4. FIRST AID MEASURES

Signs and symptoms of exposure: Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, coughing. Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

Medical conditions aggravated by exposure: Skin, kidney and respiratory conditions.

Emergency first aid procedures:

Skin: Flush with water immediately - Seek medical attention if necessary

Eyes: Flush with water for 15 minutes - Seek medical attention

Ingestion: DO NOT induce vomiting, drink large amounts of water - seek medical attention. Never give anything by mouth to an unconscious person

Inhalation: Remove to fresh air. Support respiration if required - Seek medical attention

5. FIREFIGHTING MEASURES

Extinguishing media: dry chemical.

Special fire fighting procedures: use self sustaining respiratory suit.

Unusual Fire and Explosion Hazards: May release Toxic metal & oxide fumes. High concentrations of dust may present explosion hazard. Water trapped below molten may explode thus spattering molten metal.

6. ACCIDENTAL RELEASE MEASURES

Methods and materials: Flush into chemical sewer or sweep up with a suitable absorbent. Wear adequate protection as described in section 8.

Environmental Precautions: Avoid release to the environment. Collect spillage.

7. HANDLING & STORAGE

Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Keep out of the reach of children. Read label and SDS prior to use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limit Values: See section 3.

Respiratory Protection (type): HEPA mask required for fumes above TWA.

Ventilation: Local Exhaust preferred Special: NE

Mechanical: OK Other: NE

Protective Gloves: plastic or rubber Eye Protection: Goggles or face shield

Other Protective Clothing or Equipment: as required to avoid contact.

Work/Hygienic Practices: Wash after use. Follow good industrial hygienic practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 2840 F

Specific Gravity: 7.0

Vapor Pressure (mm Hg): NE

Melting: <200F

Vapor Density: NE

Evaporation Rate: <1 (butyl acetate=1)

Solubility in water: negligible

pH: NE

Flash Point: NE (TOC)

Flammable Limits: lcl: NE ucl: NE

Appearance and odor: Silver/Grey solid, odorless.

10. STABILITY AND REACTIVITY

Stability : STABLE Conditions to avoid : none

Incompatibility (materials to avoid): strong bases & acids, oxidizers, sulfides, halogens.

Hazardous Decomposition or Byproducts (incomplete combustion): May release Toxic metal & oxide fumes. High concentrations of dust may present explosion hazard. Water trapped below molten may explode thus spattering molten metal.

Hazardous Polymerization: WILL NOT OCCUR Conditions to avoid: none

11. TOXICOLOGICAL INFORMATION

Routes of entry: Inhalation: no Skin: no Ingestion: yes

Health Hazards (acute and chronic):

Gross ingestion maybe toxic and can result in death. Symptoms of toxicity may take hours to manifest. Ingestion may result in kidney, red blood cell, reproductive and nervous system effects.

Carcinogenicity: not determined NPT? no IARC Monographs? Lead-suspect

12. ECOLOGICAL INFORMATION

Toxicity: NE
Bio-accumulative Potential: NE
PBT & vPvB Assessment: NE

Persistence & Degradability: NE
Mobility in Soil: NE
Other Adverse Effects: NE

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: dispose of in accordance with all local state and federal regulations

Other Precautions: Avoid skin & eye contact, inhalation & ingestion of fumes and material. Wash contaminated clothing before reuse. Keep away from children.

14. TRANSPORT INFORMATION

DOT Classification: Non-Hazardous
Marine Pollutant: NE

15. REGULATORY INFORMATION

NFPA Classification (NFPA 325M, 8th edition)(Health, Flammability, Reactivity): 2-0-0
This product contains components known to the state of California to cause cancer or reproductive harm.

16. OTHER INFORMATION

The information and recommendations contained within the publication have been compiled from sources believed to be reliable and to represent the best information available to **SRA Soldering Products** at the time of issue. No warranty, guarantee, or representation is made by **SRA Soldering Products** nor does **SRA Soldering Products** assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances.

NE = not established NA = not applicable

Revision Date 01/28/2022