


PROPRIETARY INFORMATION:
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR
 USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY
 PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	09/15/18	BS



GENERAL SPECIFICATIONS:

RATING: 7A / 125V
 CABLE TYPE / SIZE: SVT, AWG 18 X 3 CONDUCTORS
 TEMPERATURE RATING: 60°C
 CONDUCTOR COLORS: BLACK / WHITE / GREEN
 CABLE JACKET COLOR: BLACK
 OVERALL LENGTH (L): 2500± 20 mm
 CABLE OUTER DIAMETER: 6.3 ± 0.15 mm
 END 'A' PLUG: IEC 320 / C13 FEMALE DOWN ANGLE
 END 'B': CUT BLUNT
 APPROVALS CABLE: UL
 APPROVALS CONNECTOR: UL


PACKING:
 BULK PACK

NOTES:
 1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



RELEASED
 By N.Frost at 8:11 am, Sep 18, 2018



DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
TABULATION BLOCK				
REV.			TOLERANCES: DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005	 GlobTek, Inc. www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111
SHEET				
INIT.BY: BS	DATE: 09/15/18		MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/- .013	DWG TITLE: NORTH AMERICAN DOWN ANGLE IEC320/C13 CORDSET
DRAWN: NF	DATE: 09/15/18	FSCN No.: G, CC	SIZE: A	REV. A
APRVD: BS	DATE: 09/15/18	SCALE: NONE	PART NO: 7011432M500-EL7012(R)	SHEET 1/1

Foot Note:
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice