

Data sheet | Item number: 756-5401/040-020




Sensor/Actuator cable; M12A socket; straight; M12A plug; straight; 4-pole;
Length: 2 m



www.wago.com/756-5401/040-020



 Picture differs from the item.



Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

Data

Technical data

General

Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	2.5 kV
Contact resistance	10 mΩ
Conductor resistance	≤ 60 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Suitable for drag chains

Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

Cable

Cable length	2 m
Type code	LiF9YH-11YH or LiF9YC11YFHF
Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	4.5 ... 4.9 mm

Connector

Connection type	M12 Socket - M12 plug
Cable connection direction to mating direction	0°
Cable connection direction to mating direction (2)	0°

Subject to changes. Please also observe the further product documentation!



Connector interface coding (cable/adapter) 1 1	A-coded
Connector interface coding (cable/adapter) 2 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	1 Nm

Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	HU
GTIN	4044918975520
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	b6424334-ae9a-4962-8c9d-d1b31506c1cd
SCIP notification number (Belgium)	4f1eded9-bdd1-4fa0-be96-51a5964748f4
SCIP notification number (Bulgaria)	93270d10-883d-4ef8-83ee-fb9c7cc4753d
SCIP notification number (Czech Republic)	47260a0b-d1cf-45b2-b3ac-2b44ffb9aaa1
SCIP notification number (Denmark)	977ffbde-8b03-4dc4-88d1-72464cf3d006
SCIP notification number (Finland)	f4891b32-d08b-4b4e-b31a-e0bca7894e13
SCIP notification number (France)	e0f81532-5bca-42ef-9a38-0d058d3c0a3a
SCIP notification number (Germany)	7140522a-6be3-40bb-9804-9d65608d1087
SCIP notification number (Hungary)	e8ec6be6-719a-46bb-b4be-9a09e80e1da1
SCIP notification number (Italy)	c8024a24-c4a9-4f00-9ee5-6a783e72ab56
SCIP notification number (Netherlands)	ccd340f-cde7-4db9-be71-c413a8a2792c
SCIP notification number (Poland)	1158b4f5-a8ed-46f9-a14c-bbe1b92d2459
SCIP notification number (Romania)	b352e67a-36ab-4822-8f68-b5f3e0d4a909
SCIP notification number (Sweden)	5f88146e-ac3c-4d4e-a6d4-d2f80f23feed


Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Documentation

Bid Text

756-5401/040-020 X81 - Datei	2019 Feb 19	xml 3.3 kB	Download
756-5401/040-020 doc - Datei	2017 Sep 20	doc 27.1 kB	Download

System Description

IP67 Cables and Pluggable Connectors	pdf 161.6 kB	Download
--------------------------------------	-----------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 756-5401/040-020	URL	Download
WSCAD Universe 756-5401/040-020	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-5401/040-020 Sensor/Actuator cable; M12A socket; straight; M12A plug; straight; 4-pole; Length: 2 m	URL	Download
---------------------------------------------------------------------------------------------------------------------------------------------	-----	----------

Subject to changes. Please also observe the further product documentation!



Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.