

## FEATURES

- High Pulse Power Capability
- Low ESR
- Low Leakage Current
- Large capacitance for high energy density
- No Explosion Safety

## APPLICATIONS

- Camera Flash Systems ,Energy Harvesting ,GSM/GPRS Pulse Applications ,UPS/Industrial ,Wireless Alarms ,Remote Metering ,Scanners ,Toys and Games.



## OPERATING TEMPERATURE RANGE

Operating temperature	7.5V Series		8.1V Series		9.0V Series	
	Balanced	Unbalanced	Balanced	Unbalanced	Balanced	Unbalanced
-40°C to +65°C	7.5V	7.0V	8.1V	7.5V	9.0V	8.1V
-40°C to +85°C	6.4V	5.9V	6.9V	6.4V	/	/


\*With appropriate voltage operating temperature can be extended to 85°C

## GENERAL SPECIFICATIONS


Item	Performance
Operating temperature	-40°C to +65°C
Capacitance range	0.33F to 6.5F
Capacitance tolerance	-10% to+30%:-0% to+100%
Rated voltage	7.5 V/8.1 V/9.0 V
Temperature characteristics	Capacitance change: Within ±30% of initial measured value at +25°C Internal resistance: Within ±200% of initial measured value at +25°C
High temperature load time	After 65°C 1500 hours Capacitance change: ±30% of initial rated value Internal resistance: Within 2 times of initial specified value
Projected cycle life (From rated voltage to 1/2 rated voltage at 25°C)	After 500,000 cycles: Capacitance change: Within ±30 % of initial rated value Internal resistance: Within 2 times of initial specified value
Humidity characteristic	Relative humidity: 90%~95% /Duration of testing:240 hrs /Temperature:40±2°C Capacitance change: Within ±30 % of initial rated value Internal resistance: Within 2 times of initial specified value
Vibration resistance	Amplitude:1.5mm /Frequency:10~55Hz /Duration of testing:6 hrs Capacitance change: Within ±30 % of initial rated value Internal resistance: Within 2 times of initial specified value
Shelf life	After 2 years at 25°C without load, the capacitor shall meet the specified endurance limits.

**DIMENSIONS**


**DA Type:**



**PC Type:**



**DZ Type: RADIAL BENT LEAD**



Cell Dia	D	W	P(mm)		Φd
			DA Type	PC Type	
Φ8	8	24	20.5	13.5	0.6
Φ10	10	31	26.5	16.5	0.6
Φ12.5	12.5	28	31.5	22.5	0.6

Cell Dia	DZ Type		Φd
	P(mm)	B(mm)	
Φ8	13.5	2.0	0.6
Φ10	16.5	2.0	0.6
Φ12.5	22.5	2.0	0.6

\*for version with bent leads


**STANDARD PRODUCTS**

Part Number	Rated Voltage (V)	Rated Cap (F)	Size ΦWxDxL (mm)	Max.ESR		Maximum Endurance Current(A)	Maximum Peak Current(A)	Maximum Leakage Current (72hrs/mA)	Power Density (W/Kg)	Maximum Energy (W.h)	Energy Density (Wh/kg)
				ESRAC (1kHz/mΩ)	ESRDC (mΩ)						
CZP-7R5L334R-TW	7.5	0.33	24*8*14	450	900	0.38	0.99	0.006	2419	0.0026	0.9
CZP-7R5L604R-TW		0.6	24*8*18	225	450	0.45	1.77	0.009	3947	0.0047	1.4
CZP-7R5L105R-TW		1	24*8*22	180	360	0.56	2.76	0.011	4076	0.0078	2.0
CZP-7R5L155R-TW		1.5	32*11*22	300	600	0.79	3.65	0.0020	1607	0.0117	1.7
CZP-7R5L225R-TW		2.2	32*11*22	250	500	0.93	4.61	0.0023	1731	0.0172	2.2
CZP-7R5L335R-TW		3.3	32*11*31	200	330	1.24	5.33	0.030	2351	0.0258	3.0
CZP-7R5L505R-TW		5	38*13*28	160	260	1.80	10.66	0.055	1923	0.0391	2.9
CZP-7R5L655R-TW		6.5	38*13*28	150	220	1.95	11.25	0.007	1918	0.0508	3.2
CZP-8R1L334R-TW	8.1	0.33	24*8*14	500	2900	0.24	0.69	0.007	897	0.0030	0.98
CZP-8R1L604R-TW		0.6	24*8*18	400	1100	0.41	1.47	0.009	1934	0.0055	1.45
CZP-8R1L105R-TW		1.0	24*8*22	350	850	0.50	2.20	0.012	1986	0.0091	1.93
CZP-9R0L334R-TW	9.0	0.33	24*8*14	500	2900	0.26	0.77	0.007	1072	0.0037	1.17
CZP-9R0L604R-TW		0.6	24*8*18	400	1100	0.38	1.64	0.012	2308	0.0068	1.73
CZP-9R0L105R-TW		1.0	24*8*22	350	850	0.53	2.45	0.018	2338	0.0113	2.27


Note: Adds passive balance. Balance options can be provided upon request. Customers can choose according to the application.

### QUALITY AND RELIABILITY


CAPACITANCE VS. TEMPERATURE



LEAKAGE CURRENT VS. TEMPERATURE



EQUIVALENT SERIES RESISTANCE VS. TEMPERATURE



## LIFE TIME AND TEMPERATURE PERFORMANCE

The life of a Super Capacitor is impacted by a combination of operating voltage and the operating temperature according to the following equation :

$$LS = L_R \times 2^X \times 2^Y$$

Which is  $X = (T_m - T_a) / 10$   $Y = (V_r - V_a) / 0.2$

$L_s$  = Expected life of the super capacitor in the application


$L_R$  = Load life rating of the super capacitor

$T_m$  = Max temperature rating of the super capacitor

$T_a$  = Ambient temperature of the application

$V_r$  = Rated voltage of the super capacitor

$V_a$  = Maximum applied voltage on the super capacitor in the application





CZP(7.5V~9.0V) Series



Connected Module Series

www.cda-cap.com

## SAFETY RECOMMENDATIONS

### WARNINGS

- To Avoid Short Circuit, after usage or test, SuperCapacitors voltage needs to discharge to  $\leq 0.1V$
- Do not Apply Overvoltage, Reverse Charge, Burn or Heat Higher than  $150^{\circ}C$ , explosion-proof valve may break open
- Do not Press, Damage or disassemble the SuperCapacitor, housing could heat to high temperature causing Burns
- If you observe Overheating or Burning Smell from the capacitor disconnect Power immediately, and do not touch

### REGULATORY

- MSDS
- RoHS Compliant
- Reach Compliant

### TRANSPORTATION

Not subjected to US DOT or IATA regulations  
 UN3499, <10Wh, Non-Hazardous Goods  
 International shipping description –  
 “Electronic Products – Capacitor”

## PRECAUTIONS FOR WELDING

When soldering supercapacitors to a PCB, the temperature & time that the body of the supercapacitor sees during soldering can have a negative effect on performance. We advise following these guidelines:

- Do not immerse the supercapacitors in solder. Only the leads should come in contact with the solder.
- Ensure that the body of the supercapacitor is never in contact with the molten solder, the PCB or other components during soldering.
- Excessive temperatures or excessive temperature cycling during soldering may cause the safety vent to burst or the case to shrink or crack, potentially damaging the PCB or other components, and significantly reduce the life of the capacitor.

### HAND SOLDERING

Keep distance between the supercapacitor body and the tip of the soldering iron and the tip should never touch the body of the capacitor. Contact between supercapacitor body and soldering iron will cause extensive damage to the supercapacitor, and change its electrical properties. It is recommended that the soldering iron temperature should be less than  $350^{\circ}C$ , and contact time should be limited to less than 4 seconds. Too much exposure to terminal heat during soldering can cause heat to transfer to the body of the supercapacitor, potentially damaging the electrical properties of the supercapacitor.

### WAVE SOLDERING

Only use wave soldering on Radial type supercapacitors. The PCB should be preheated only from the bottom and for less than 60 seconds, with temperature at, or below,  $100^{\circ}C$  on the top side of the board for PCBs equal to or greater than 0.8 mm thick.

Solder Temperature ( $^{\circ}C$ )	Suggested Solder Time (s)	Maximum Solder Time (s)
220	7	9
240	7	9
250	5	7
260	3	5

### REFLOW SOLDERING

Infrared or conveyor over reflow techniques can be used on these supercapacitors. Do not use a traditional reflow oven without clear rated reflow temperature for supercapacitors.