

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

ltc1596aisw#pbf

(Engineering Calculation)

SOIC WIDE

(printed on: 2020-07-11 19:12:51)

**TOTAL MASS (g) : 0.24939**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.004583	1000000	18376.8144531		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.138021	975000	553433.625		
		Iron (Fe)	7439-89-6	0.003397	24000	13621.2158203		
		Phosphorus (P)	7723-14-0	0.000042	300	168.410690308		
		Zinc (Zn)	7440-66-6	0.000099	700	396.968017578		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.141559</b>	<b>1000000</b>	<b>567620.1875</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.004771	1000000	19132.1269531		
		<b>External Plating Total:</b>				<b>0.004771</b>	<b>1000000</b>	<b>19132.1269531</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.001132	1000000	4539.06884766		
<b>Internal Plating Total:</b>				<b>0.001132</b>	<b>1000000</b>	<b>4539.06884766</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.001231	750000	4936.03662109		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000410	250000	1644.0090332		
<b>Die Attach Total:</b>				<b>0.001641</b>	<b>1000000</b>	<b>6580.04589844</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.009816	103000	39359.984375		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.085294	895000	342010.03125		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000000	0	0		
		Carbon Black (C)	1333-86-4	0.000191	2000	765.867614746		
		<b>Encapsulation Total:</b>				<b>0.095301</b>	<b>1000000</b>	<b>382135.875</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000403	1000000	1615.94055176		
					<b>TOTAL MASS (g) :</b>	<b>0.24939</b>		