

T495B474M035ZTA2K5

Obsolete

B45197A, Tantalum, MnO₂ Tantalum, .47 uF, 20%, 35 VDC, SMD, Molded, Low ESR, Surge Robust, 2.5 Ohms, 3528, Height Max = 2.1mm



General Information

Series	B45197A
Dielectric	MnO ₂ Tantalum
Style	SMD Chip
Description	SMD, Molded, Low ESR, Surge Robust
Features	Low ESR, Surge Robust, Automotive
RoHS	Yes
Termination	Tin
AEC-Q200	No
Notes	Obsolete.

Specifications

Capacitance	.47 uF
Capacitance Tolerance	20%
Voltage DC	35 VDC (85C), 23.45 VDC (125C)
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	4%
Failure Rate	N/A
Resistance	2.5 Ohms (100kHz)
Ripple Current	180 mAmps (25C), 162 mAmps (85C), 72 mAmps (125C)
Leakage Current	0.2 uA

Dimensions

Footprint	3528
L	3.5mm +/-0.2mm
W	2.8mm +/-0.2mm
H	1.9mm +/-0.2mm
S	0.7mm +/-0.3mm
F	2.2mm +/-0.1mm
K	1.4mm TYP

Packaging Specifications

Packaging	T&R, 178mm
Packaging Quantity	2000