




VMTSC75-25-M12-55-S

Ruland VMTSC75-25-M12-55-S, Vibration Isolation Mount, 75mm OD, M12 Threaded Stud, M12 Tapped Hole, 37mm Stud Length, 12mm Tapped Hole Depth, 25mm Height, 55 Shore A Natural Rubber Jacket, Stainless Steel



Description

Ruland VMTSC75-25-M12-55-S is a vibration isolation mount with one tapped hole and one threaded stud. It has a 75mm outside diameter, M12 threaded stud, M12 tapped hole, 37mm stud length, 12mm tapped hole depth, and 25mm height. This vibration isolation mount is used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. It is often referred to as a sandwich mount or rubber buffer because it functions as shock or vibration isolator sandwiched between two machine components or surfaces. The threaded stud side of VMTSC75-25-M12-55-S can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped hole on the component it will be mounted to. The tapped hole can be mounted to the system by threading it onto an existing stud on the component. VMTSC75-25-M12-55-S has a rubber jacket that is made from natural rubber which has good elasticity and is well suited for most industrial equipment. It has 55 Shore A hardness for a balance of rigidity and shock absorption. The stainless steel body allows for increased corrosion resistance. VMTSC75-25-M12-55-S is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	2.95 in (75 mm)	Height (H1)	0.98 in (25 mm)
Thread (TH)	M12 x 1.75	Plate Thickness (PT)	0.12 in (3 mm)
Stud Length (LS)	1.46 in (37 mm)	Tapped Hole Depth (LT)	0.47 in (11.9 mm)
Spring Rate	10049.86 lb/in (1760 N/mm)	Shore Hardness	55A (+/- 5)
Max Deflection	0.25 in (6.4 mm)	Max Axial Load	2472.9 lb (11000 N)
Geometry	Cylindrical	Rubber Material	Natural Rubber
Metal Material	Stainless Steel	Metallic Body Finish	Bright
Country of Origin	Hungary	Weight (lbs)	0.617300
UPC	634529364666	Tariff Code	4016.99.6000
UNSPC	31162804		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		