

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
D		REVISED PER ECO-17-002903	20MAR2017	AP DG

1 RECEPTACLE ACCEPTS SIZE 22 DF SOCKET CONTACTS. CONTACTS MUST BE PURCHASED SEPARATELY.

2 ALL PARTS SHIPPED UNASSEMBLED.

3 FLAME RETARDANT 94V-0 RATED, STYRENE POLYOLEFIN OR PVC, BLACK.

4 FLAME RETARDANT 94V-0 RATED, GLASS FILLED NYLON OR POLYESTER, BLACK.

5 STEEL PER ASTM A109.

6 TIN PLATING PER MIL-T-10727.

7 BLACK ZINC FLAKE COATING.

8 COMPONENTS INDIVIDUALLY BULK PACKED.

9 CARBON STEEL, C1022.

EXPANDING NECK, ACCOMMODATES CABLE FROM .190-.375 DIA

1.685 MAX

FERRULE, MUST BE PURCHASED SEPARATELY, AS REQUIRED BY CABLE DIAMETER

4-40 JACKSCREW QTY: 2

SHIELD QTY: 2

ENCLOSURE

RCPT CONNECTOR HDP-22

1.467 TYP

.812 TYP

1.630 MAX

CABLE REF

.125 MAX

1.640 MAX

1.312 ± .005

W/ LOGOS	8	1658689-1
REMARKS	PACKAGING	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 13AUG07 J. POLIGNONE	TE Connectivity	
DIMENSIONS: INCHES		CHK 13AUG07 C. ROHDE	SHIELDING ENCLOSURE KIT, RCPT, SIZE 2, 26 POSN, HDP-22, AMPLIMITE	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 13AUG07 C. ROHDE	NAME	
0 PLC ± -	1 PLC ± -	PRODUCT SPEC	SIZE	CAGE CODE
2 PLC ± -	3 PLC ± .020	APPLICATION SPEC	A2	00779
4 PLC ± -	ANGLES ± -	WEIGHT	DRAWING NO	
MATERIAL	FINISH	0.000000	C=1658689	
3 4 5 9	6 7	CUSTOMER DRAWING	SCALE 2:1	SHEET 1 of 1
			REV D	

1471-9 (1/15)

1658689

A