

## Up-Angle Cat6 Gigabit Molded UTP Ethernet Cable (RJ45 Right-Angle Up M to RJ45 M), Blue, 5 ft. (1.52 m)

MODEL NUMBER: N204-005-BL-UP



### Highlights

- Space saving design
- Up Angle connector to Straight
- Cat6 Gigabit rated

### System Requirements

- Use with Cat6, Cat5e, Cat5, or VoIP Networks

### Package Includes

5-ft. (1.52 m) Blue Cat6 Up Angle to Straight RJ45 - RJ45 Patch cable

### Features

- 5-ft. (1.52 m) Blue Cat6, Up Angle to Straight RJ45 - RJ45 Patch cable
- PVC 4 Pair Stranded Conductors, 24AWG
- Fully Molded Ends
- ETL Verified to TIA/EIA -568-B
- 550Mhz Gigabit Speed Rated

## Specifications

| OVERVIEW              |                 |
|-----------------------|-----------------|
| UPC Code              | 037332167576    |
| Technology            | Cat6            |
| PHYSICAL              |                 |
| Color                 | Blue            |
| Cable Shielding       | UTP             |
| Cable Jacket Material | PVC             |
| Cable Jacket Rating   | CM              |
| Number of Conductors  | 4 Pair          |
| Conductor Material    | Stranded Copper |



|                                      |                           |
|--------------------------------------|---------------------------|
| Conductor Gauge                      | 24 AWG                    |
| Cable Length (ft.)                   | 5                         |
| Cable Length (m)                     | 1.5                       |
| Cable Length (in.)                   | 60                        |
| Cable Length (cm)                    | 152.4                     |
| Shipping Dimensions (hwd / cm)       | 22.86 x 17.78 x 1.27      |
| Shipping Dimensions (hwd / in.)      | 9.00 x 7.00 x 0.50        |
| Shipping Weight (kg)                 | 0.07                      |
| Shipping Weight (lbs.)               | 0.16                      |
| <b>COMMUNICATIONS</b>                |                           |
| Bandwidth per TIA Standard           | 250 MHz                   |
| Maximum Bandwidth as Tested          | 500 MHz                   |
| Maximum Data Rate                    | 1Gbps                     |
| <b>CONNECTIONS</b>                   |                           |
| Side A - Connector 1                 | RJ45 (MALE)               |
| Side B - Connector 1                 | RJ45 (MALE) - UP ANGLE    |
| Connector Type                       | Molded                    |
| Wiring Configuration                 | EIA/TIA 568B              |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                           |
| Cable Style                          | Unshielded; Molded        |
| <b>SPECIAL FEATURES</b>              |                           |
| IP68 Rated                           | No                        |
| Snagless Connector                   | No                        |
| Antibacterial                        | No                        |
| <b>WARRANTY</b>                      |                           |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>