

# FL COMSERVER PRO 232/422/485

Order No.: 2313465




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2313465>

FL COMSERVER PRO..., freely programmable in BASIC, to create one's own solution for converting a serial RS-232/422/485 interface to Ethernet incl. CD-ROM with examples, additional software and user documentation (PDF).

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Commercial data

GTIN (EAN)	 4 046356 451338
sales group	H651
Pack	1 pcs.
Customs tariff	85176200
Catalog page information	Page 534 (IF-2009)

## Technical data

### Serial interface

Interface 1	Ethernet interface, 10/100BASE-T(X) in acc. with IEEE 802.3u
Transmission length	100 m (shielded twisted pair)
Type of connection	RJ45 female connector, shielded
Serial transmission speed	10/100 Mbps, autonegotiation
Interface 2	V.24 (RS-232) interface in acc. with ITU-T V.28, EIA/TIA-232, DIN 66259-1
File format/coding	Serial asynchronous UART/NRZ, 7/8 data, 1/2 stop, 1 parity, 10/11-bit character length

Termination resistor	390 Ω - 180 Ω - 390 Ω (can be connected)
Type of connection	D-SUB-9 male connector
Data flow control/protocols	Software handshake, Xon/Xoff or hardware handshake RTS/CTS
Serial transmission speed	300, 600, 1200, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200, 187500, 230400 Bit/s, can be set with web-based management
Interface 3	RS-422 interface in acc. with ITU-T V.11, EIA/TIA-422, DIN 66348-1
Type of connection	Plug-in/screw connection via COMBICON
Termination resistor	390 Ω - 180 Ω - 390 Ω (can be connected)
File format/coding	Serial asynchronous UART/NRZ, 7/8 data, 1/2 stop, 1 parity, 10/11-bit character length
Data flow control/protocols	Automatic control
Serial transmission speed	300, 600, 1200, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200, 187500, 230400 Bit/s, can be set with web-based management
Interface 4	RS-485 interface, in acc. with EIA/TIA-485, DIN 66259-4/RS-485 2-wire
Interface	RS-485
Type of connection	Plug-in/screw connection via COMBICON
Termination resistor	390 Ω - 180 Ω - 390 Ω (can be connected)
File format/coding	Serial asynchronous UART/NRZ, 7/8 data, 1/2 stop, 1 parity, 10/11-bit character length
Data flow control/protocols	Automatic control
Serial transmission speed	300, 600, 1200, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200, 187500, 230400 Bit/s, can be set with web-based management
<b>Power supply</b>	
Nominal supply voltage	24 V DC ±20 % (via pluggable COMBICON screw terminal block)
	24 V DC ±5% (as an alternative or redundant, via backplane bus contact and system current supply)
Typical current consumption	100 mA (24 V DC)
<b>General data</b>	
Width	22.5 mm
Height	99 mm
Depth	114.5 mm
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Ambient temperature (operation)	-25 °C ... 60 °C
Electrical isolation	Supply // Ethernet (TP) // Serial

Test voltage data interface/power supply	1.5 kV <sub>rms</sub>
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Noise emission	EN 61000-6-4
Noise immunity	EN 61000-6-2:2005
Degree of protection	IP20
Net weight	190 g
Housing material	PA 6.6-FR
Color	green
MTBF	666 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day)) 179 Years (Telcordia standard, 40°C temperature, 34.25% operating cycle (5 days a week, 12 hours a day))

#### Function

Management	Web-based management, SNMP, serial emergency access
Status and diagnostic indicators	LEDs: UL (logic voltage), TD + RD (data activity serial), FD (full duplex), 100 (100 Mbps mode), Link (Ethernet), Activity (Ethernet), ERR (error)

#### Certificates / Approvals



Certification

CUL Listed, UL Listed

#### Accessories

Item	Designation	Description
<b>Assembly</b>		
2853899	ME-SAS	Shield connection clamp for printed circuit terminal block
<b>Cable/conductor</b>		
2881078	CM-KBL-RS232/USB	Connecting cable D-9-SUB to USB, with adapter D-9-SUB to D-25-SUB.

2744827	FL CAT5 HEAVY CONF/	CAT5-SF/UTP cable (J-02YS(ST)C HP 2 x 2 x 24 AWG), heavy-duty installation cable, 2 x 2 x 0.22 mm <sup>2</sup> , solid conductor, shielded, outer sheath: 7.8 mm diameter, inner sheath: 5.75 mm ± 0.15 mm diameter, preassembled on both sides with RJ45 plug, crossover or line
2832263	FL CAT5 PATCH 0,5	Patch cable, CAT5, assembled, 0.5 m
2832580	FL CAT5 PATCH 5,0	Patch cable, CAT5, assembled, 5.0 m
2761059	PSM-KA 9 SUB 25/BB/2METER	RS-232 cable, 9-pos. D-SUB female connector 25-pos on D-SUB female connector
2799474	PSM-KA9SUB9/BB/2METER	RS-232 cable, 9-pos. D-SUB female connector on 9-pos. D-SUB female connector, 9-wire, 1:1
2319200	PSM-KAD-IL RS232/9SUB/B/0,8M	Adapter cable to connect the IB IL RS232 and IB IL RS232-PRO Inline communication terminals to the interface converter, e.g. modem, Com server, Bluetooth or fiber optics.

#### General

2891246	FL PATCH SAFE CLIP	Security element for FL patch cable
2707437	ME 22,5 TBUS 1,5/ 5-ST-3,81 GN	DIN rail connector for current transducers, gold-plated contacts, for DIN rail mounting, 5-pos.
2866983	MINI-SYS-PS-100-240AC/24DC/1.5	DIN rail power supply unit, primary-switched mode, slim design, output: 24 V DC / 1.5 A

#### Software

2831044	FL SWT	Factory Manager, multilingual, configuration and diagnostics software for ETHERNET networks in automation
---------	--------	---

#### Tools

1204517	SZF 1-0,6X3,5	Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip
---------	---------------	---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;