



Metric table

Dimensions in: millimeters - inches

1 d ₁	2 d ₂ Thread			d ₃	h ₁	h ₂	t
	M 4	M 5	M 6				
20 .79	M 4	M 5	M 6	13 .51	15 .59	7 .28	9 .35
30 1.18	M 5	M 6	-	17 .67	24 .94	11 .43	9 .35
30 1.18	M 8	-	-	17 .67	24 .94	11 .43	15 .59
40 1.57	M 6	-	-	21 .83	28 1.10	12 .47	13 .51
40 1.57	M 8	-	-	21 .83	28 1.10	12 .47	15 .59
40 1.57	M 10	-	-	21 .83	28 1.10	12 .47	16 .63
50 1.97	M 8	-	-	25 .98	33 1.30	13 .51	15 .59
50 1.97	M 10	-	-	25 .98	33 1.30	13 .51	16 .63
50 1.97	M 12	-	-	25 .98	33 1.30	13 .51	18 .71

Specification

- Six-lobed knob
Phenolic plastic
- Temperature resistant up to 300 °F (150 °C)
- Black, shiny finish
- Tapped insert
Brass, molded-in
- RoHS compliant

Information

The solid design of the VB six-lobed knobs is an excellent choice for food applications or any application where bacteria accumulation is unwanted.

see also...

- Six-Lobed Knobs VB-FP (with Tapped Through Insert)
- Six-Lobed Knobs VP (with Steel Threaded Stud)

On request

- For certain minimum quantities, stainless steel inserts

How to order 1 2 VB-20-M5	1 Handle diameter d ₁
	2 Thread d ₂