

LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

| Connector dimension |          |
|---------------------|----------|
| Dim                 | Nominal  |
| ØS                  | 38.5 Max |
| Z                   | 31 Max   |
| VV THREAD           | M28x1-6g |

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Stainless Steel
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +200°C
- Salt Spray : 500 hours
- Mass : 83.63 g ± 10%

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)


| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D519S11PBL**

|              |  |                                     |   |
|--------------|--|-------------------------------------|---|
| A            | 18-10-2016   | First Release                       |   |
| ISS          | DATE   | Latest modification - by            | MOD N°  |
| Designed By: |  | Date:                               | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b> | <b>Stainless Steel Plug 8D series</b>                |                                     |   |
| SCALE        |  | General linear Tolerances: ±--      | NPRDS / PROJECT<br><b>859</b>   |
| NA           | <a href="http://WWW.SOURIAU.COM">WWW.SOURIAU.COM</a> |                                     | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT       | <b>A3</b>  |                                     | SHEET<br>1/2  |
|              |  | <b>SOURIAU DRG N° 8D519S11PBL-C</b> |   |

|                |                         |   |   |    |                                 |    |   |   |   |                        |
|----------------|-------------------------|---|---|----|---------------------------------|----|---|---|---|------------------------|
| BASIC SERIES:  | 8D                      | 5 | - | 19 | S                               | 11 | P | B | L | Delivered W/O Contacts |
| SHELL TYPE :   | Plug with RFI Shielding |   |   |    | ORIENTATION : B                 |    |   |   |   |                        |
| CONTACT TYPE : | Standard Crimp Contact  |   |   |    | CONTACT TYPE : PIN(500 Matings) |    |   |   |   |                        |
| SHELL SIZE :   | 19                      |   |   |    | CONTACT LAYOUT : 19-11          |    |   |   |   |                        |
| PLATING :      | S = Nickel              |   |   |    |                                 |    |   |   |   |                        |

Contact Layout



| Contact position ID | Location    |             | Contact position ID | Location    |             |
|---------------------|-------------|-------------|---------------------|-------------|-------------|
|                     | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |
| A                   | +105 (2.67) | +260 (6.60) | G                   | -275 (6.99) | -053 (1.35) |
| B                   | +250 (6.35) | +132 (3.35) | H                   | -250 (6.35) | +132 (3.35) |
| C                   | +275 (6.99) | -053 (1.35) | J                   | -105 (2.67) | +260 (6.60) |
| D                   | +179 (4.55) | -215 (5.46) | K                   | +000 (0.00) | +105 (2.67) |
| E                   | +000 (0.00) | -281 (7.14) | L                   | +000 (0.00) | -092 (2.34) |
| F                   | -179 (4.55) | -215 (5.46) | ---                 | ---         | ---         |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 19         | -11             | 11                 | 16            | II             | All              | MS20054-11 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D519S11PBL

|                |                                       |                                |  |
|----------------|---------------------------------------|--------------------------------|--|
| A              | 18-10-2016                            | First Release                  |  |
| ISS            | DATE                                  | Latest modification - by       | MOD N°   |
| Designed By:   |                                       | Date:                          | <b>CUSTOMER DRAWING</b>  |
| <b>TITLE</b>   | <b>Stainless Steel Plug 8D series</b> |                                |  |
| SCALE          |                                       | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                                | This document is the property of SOURIAU<br>it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D519S11PBL-C</b>   |                                | SHEET<br>2/2   |