



3M™ High Temperature Aluminum Foil Tape 433

Last Revision Date: May, 2022

Product Description

3M™ High Temperature Aluminum Foil Tape 433 has a silicone adhesive that can be used in many high temperature applications. Also comes in an easy-release film liner (3M™ High Temperature Aluminum Foil Tape 433L).

Product Features


- Flame resistant – meets requirements of FAR 25.853(a).
- 3M™ High Temperature Aluminum Foil Tape 433L can easily be die-cut into special sizes or shapes.
- Best results obtained when applied to a clean surface above 32°F (0°C), but tape can be applied from 0°F to 200°F (-18°C to 93°C).
- Performance range from -65°F to over 600°F (-54°C to over 316°C). Adhesive will gradually thermoset at high temperatures. As it thermosets, the adhesive mass becomes firm and gradually loses its pressure sensitivity but will continue to hold the tape in place.

Technical Information Note






The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values	Additional Information
Backing	Aluminum Foil	
Adhesive Type	Silicone (clear)	
Color	Silver	
Backing Thickness	0.05 mm	View
Test Method: ASTM D3652		
Total Tape Thickness	3.6 mil	View
Test Method: ASTM D3652		
Total Tape Thickness	0.09 mm	View
Test Method: ASTM D3652		

Backing Thickness	2 mil	View 
Test Method: ASTM D3652		
Approximate Weight	4.4 g/m/24 mm	
Approximate Weight	0.0094 lb/yd/in	

Typical Performance Characteristics

Property	Values	Additional Information
Tensile Strength	35 N/cm	View 
Test Method: ASTM D3759		
180° Peel Adhesion	4.4 N/cm	View 
Test Method: ASTM D3330		
Notes: 12 in/min (300 mm/min)		
180° Peel Adhesion	40 oz/in	View 
Test Method: ASTM D3330		
Notes: 12 in/min (300 mm/min)		
Tensile Strength	20 lb/in	View 
Test Method: ASTM D3759		
Elongation at Break	3.5 %	View 
Test Method: ASTM D3759		
Long Term Temperature Resistance	316 °C	
Minimum Long Term Temperature Resistance	-54 °C	
Long Term Temperature Resistance	600 °F	
Minimum Long Term Temperature Resistance	-65 °F	

Temperature Use Range	-54 - 190 °C
-----------------------	--------------

Temperature Use Range	-65 - 375 °F
-----------------------	--------------

Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

To obtain best performance, use this product within 24 months from date of manufacture.

Industry Specifications

FAR 25.853(a)

Bottom Matter

3M

Industrial Business

Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue

St. Paul, MN 55144-1000

800-362-3550 • 877-369-2923 (fax)

www.3M.com

Automotive Disclaimer

Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, including, but not limited to, automotive electric powertrain battery or high voltage applications. This product does not fully adhere to typical automotive design or quality system requirements, such as IATF 16949 or VDA 6.3. This product may not be manufactured in an IATF certified facility and may not meet a Ppk of 1.33 for all properties. The product may not undergo an automotive production part approval process (PPAP). Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's automotive application and for conducting incoming inspections before use of the product. Failure to do so may result in injury, death, and/or harm to property. No written or verbal statement, report, data or recommendation by 3M related to automotive use of the product shall have any force or effect unless in an agreement signed by the Technical Director of 3M's Automotive Division. Customer assumes all responsibility and risk if customer chooses to use this product in an automotive electric powertrain battery or high voltage application, and 3M will not be liable for any loss or damage arising from or related to the 3M product or customer's use of the product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity or recall costs), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability. In no event shall 3M be liable for any damages in excess of the purchase price paid for the product.

NOTWITHSTANDING ANY OTHER STATEMENT TO THE CONTRARY, 3M MAKES NO REPRESENTATIONS, WARRANTIES OR CONDITIONS WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT IF USED IN AN AUTOMOTIVE ELECTRIC POWERTRAIN BATTERY OR HIGH VOLTAGE APPLICATION, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY ON PERFORMANCE, LONGEVITY, SUITABILITY, COMPATIBILITY, OR INTEROPERABILITY, OR ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

Handling/Application Information

Application Examples

- Moisture barrier around doors and windows to help prevent fogging of glass.
- To hold insulation on hot air ducts in industry.
- Cover resistance wire heating elements to distribute the heat.
- Splice jumbo rolls of aluminum foil or holding the last lap of narrow width rolls in preparation to annealing the rolls.
- Ideal as a heat reflective wrap along or over insulations, applied to tubes, engine support structures, missile ground handling equipment, or as a protector from other heat source areas such as hot areas in steel mills.
- Good holding, splicing, patching or general protecting tape on many applications involving high temperatures.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/p/d/b40072018/
Safety Data Sheet SDS	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=433

Family Group

Link Tags:

• [433](#)

Products	Backing	Adhesive Type	Color	Backing Thickness	Total Tape Thickness	Tensile Strength	Long Term Temperature Resistance	Minimum Long Term Temperature Resistance
433	Aluminum Foil	Silicone (clear)	Silver	0.05 mm	0.09 mm	35 N/cm	600 °F	-54 °C

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.